



Click [here](#) for the 3D model.

Dimensions

| | |
|----|-------------------|
| W | 8.26mm +/-0.38mm |
| H | 8.26mm +/-0.38mm |
| T | 4.32mm +/-0.38mm |
| S | 5.08mm +/-0.127mm |
| LL | 12.7mm +/-3.18mm |
| F | 0.64mm +/-0.03mm |
| E | 1.57mm +/-0.25mm |
| G | 0.38mm +/-0.13mm |

Packaging Specifications

| | |
|--------------------|------------|
| Packaging | T&R, 305mm |
| Packaging Quantity | 1000 |

General Information

| | |
|--------------|--|
| Series | T330 |
| Dielectric | MnO ₂ Tantalum |
| Style | Radial Molded |
| Description | Radial, Solid Tantalum, Molded |
| Features | Low Leakage |
| RoHS | No |
| Prop 65 | ⚠ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov . |
| SCIP Number | a3b4e2e1-63ea-439e-a89a-743225502a7d |
| Termination | Lead (SnPb) |
| AEC-Q200 | No |
| Construction | Molded |
| Notes | Longest Lead Is Positive. |
| Shelf Life | 156 Weeks |

Specifications

| | |
|-----------------------|--|
| Capacitance | 10 uF |
| Capacitance Tolerance | 10% |
| Voltage DC | 35 VDC (85C), 23 VDC (125C), 0.35 VDC (125C Reverse) |
| Temperature Range | -55/+125°C |
| Dissipation Factor | 6% |
| Leakage Current | 5 uA |