

## ATGBICS 81Y1618-C network transceiver module Copper 1250 **Mbit/s SFP**

Brand : ATGBICS

Product code: 81Y1618-C

Product name : 81Y1618-C

IBM Compatible Transceiver SFP 10/100/1000Base-T Copper RJ45 Connector 100m

ATGBICS 81Y1618-C network transceiver module Copper 1250 Mbit/s SFP:

ATGBICS 81Y1618 SFP operates on standard Category 5 unshielded twisted-pair copper cabling of link lengths up to 100m. IBM 1000BASE-T SFP modules support 10/100/1000 auto negotiation and auto MDI/MDIX. Our product is built to the exact specification of IBM 81Y1618= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.

ATGBICS 81Y1618-C. SFP transceiver type: Copper, Maximum data transfer rate: 1250 Mbit/s, Interface type: SFP. Product colour: Silver, Housing material: Metal, Country of origin: United Kingdom. Input voltage: 3.3 V, Maximum voltage: 4 V, Power consumption (typical): 1.3 W. Width: 13.4 mm, Depth: 56.6 mm, Height: 8.5 mm. Number of products included: 1 pc(s), Package type: Box





Performance		Features	
SFP transceiver type *CopperMaximum data transfer rate *1250 Mbit/sInterface type *SFPSingle-mode fiber (SMF) supportedXMulti-mode fiber (MMF) supportedXSFP transceiver standardTXMaximum transfer distance100 mEthernet LAN✓Copper ethernet cabling technology10BASE-T,100BASE-TX,100Auto MDI/MDI-X✓Digital Diagnostics Monitoring (DDM)X	1250 Mbit/s SFP X TX	Brand compatibility	IBM
		Power	
		Input voltage Maximum voltage Power consumption (typical)	3.3 V 4 V 1.3 W
		Operational conditions	
	10BASE-T,100BASE-TX,1000BASE-TX	Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	70 °C 0 - 70 °C -40 - 85 °C 5 - 85% 5 - 85%
		Weight & dimensions	
	Silver Metal		
Features Product colour Housing material Plug and Play Hot Plug support		Width Depth Height Weight	13.4 mm 56.6 mm 8.5 mm 24 g
Product colour Housing material Plug and Play Hot-Plug support		Depth Height	56.6 mm 8.5 mm
Product colour Housing material Plug and Play		Depth Height Weight	56.6 mm 8.5 mm
Product colour Housing material Plug and Play Hot-Plug support Hot-swap Easy to install	Metal ✓ ✓	Depth Height Weight Packaging data Number of products included	56.6 mm 8.5 mm 24 g 1 pc(s)



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.