



SMD Connectors

SMDflat 345/ 1 WS

terminal block, pin spacing: 4.00 mm, 1 pole, current rating: 6 A, voltage rating: 600 V, connection type: screwless



Order Info

reference number (ref.no.)	351101
PU	2,000 (tape-on-reel)
EAN	4028012112449

Type

type	terminal block
number of poles	1 pole
clamping units per pole	1
colour	white
connection type	screwless

Technical Data

voltage rating	600 V
current rating	6 A
impulse voltage rating	4.0 kV
voltage rating according to UL	600 V
current rating according to UL	6 A
insulating material	PPA-GF
contact material	Spring Steel, Copper
core cross-section min.	0.2 mm ²
core cross-section max.	0.75 mm ²
core cross-section min. AWG	24
core cross-section max. AWG	18
flammability rating	V-0
max. ambient temperature operation	115 °C
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	8.0-9.0 mm
pin spacing	4.00 mm
ammonia resistance	yes

Approvals

acc. to EN 60947	Download PDF
-------------------------	------------------------------

acc. to UL	Download PDF
-------------------	------------------------------

Accessories

SMDflat 345 KU/ 1	351151
--------------------------	--------

SMDflat WKZ	351199
--------------------	--------
