

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

--

ALL RIGHTS RESERVED.

© COPYRIGHT - By -

LOC

DIST

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	K2	REVISED	29MAY2015	TS	KB

プリント基板取付穴寸法図
(MOUNTING DIMENSIONS FOR P.C. BOARD)
1. 板厚, 1.6±0.15
(P.C.B. THICKNESS, 1.6±0.15)
2. 公差, ±0.1
(TOLERANCE, ±0.1)

① 相手ハウジングと所定の機能を満たして嵌合できること。
② フードの反りは0.2以内。
3. 推奨取付ねじ: JIS B 1115 又は、1122 タッピングねじ
なべ1種、呼び径3を使用し、締め付け後半田付けする。
4. 適用製品規格: 108-5093
⑤ [-A-] 面より2mmの範囲で測定。
6. 相手ハウジングとの嵌合力は、29.4N以下。
但し、リセプタクル コントクトは含まない。

① IN COUPLING WITH THE PLUG HOUSING MATING SATISFIES FUNCTION.
② WARPAGE 0.2 MAX.
3. RECOMMENDED MOUNTING SCREW: 3mm DIA,
PAN HEAD, CLASS 1 TAPPING SCREW SPECIFIED IN JIS
B1115, B1122
4. PRODUCT SPECIFICATION: 108-5093
⑤ TO BE MEASURED WITHIN 2mm FROM [-A-]
6. IN COUPLING WITH THE PLUG HOUSING MATING FORCE
29.4N MAX. WITHOUT RECEPTACLE CONTACTS.

TOLERANCE UNLESS
OTHERWISE SPECIFIED:
一般公差

0 < x ≤ 10	±0.2
10 < x ≤ 30	±0.25
30 < x ≤ 100	±0.3
ANGLE 角度	±3°

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm

MATERIAL
HOUSING: 66NYLON
TAB CONTACT: BRASSTOLERANCES UNLESS
OTHERWISE SPECIFIED:

0 PLC	±-
1 PLC	±-
2 PLC	±-
3 PLC	±-
4 PLC	±-
ANGLES	±-

SEE TABLE

DWN 7/21'92

CHK K.YUASA 7/21'92

APVD A.TOMITA 7/21'92

PRODUCT SPEC

SEE NOTE 4

APPLICATION SPEC

WEIGHT -

CUSTOMER DRAWING

L3

L2

L1

SOLDERING SIDE
半田付け部CONTACT SIDE
接触部側CONTACT FINISH
コンタクト仕上COLOR
色PART NUMBER
製品型番

26.3	4.9	4.9	SELECTIVE-TIN (MATTE)	SELECTIVE GOLD	NATURAL	5171457-5	
32.1	10.7	10.7		PRE-TIN	NATURAL	6-171457-1	
47.5	26.1	14.1		PRE-TIN	NATURAL	5-171457-1	
30.3	8.9	8.9		PRE-TIN	NATURAL	4-171457-1	
OBSOLETE	26.3	4.9	4.9	TIN-LEAD	SELECTIVE GOLD	GREEN	1-171457-4
	26.3	4.9	4.9	TIN-LEAD	SELECTIVE GOLD	NATURAL	1-171457-1
OBSOLETE	26.3	4.9	4.9	TIN-LEAD	SELECTIVE GOLD	GREEN	171457-8
OBSOLETE	26.3	4.9	4.9	TIN-LEAD	SELECTIVE GOLD	BROWN	171457-7
OBSOLETE	26.3	4.9	4.9	TIN-LEAD	SELECTIVE GOLD	BLACK	171457-6
	26.3	4.9	4.9	TIN-LEAD	SELECTIVE GOLD	NATURAL	171457-5
	26.3	4.9	4.9		PRE-TIN	GREEN	171457-4
OBSOLETE	26.3	4.9	4.9		PRE-TIN	BROWN	171457-3
OBSOLETE	26.3	4.9	4.9		PRE-TIN	BLACK	171457-2
	26.3	4.9	4.9		PRE-TIN	NATURAL	171457-1

TE Connectivity

 MULTI-INTERLOCK CONNECTOR
21P VERTICAL TYPE CAP HOUSING ASSEMBLY

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	C=171457	-

SCALE 1:1 SHEET 1 of 1 REV K2

1470-19 (3/11)