



10.70

5.80

HOUSING:	THERMOPLASTIC POLYESTER, UL94V-0		
SHELL:	STEEL, NICKEL PLATED		
CONTACT:	COPPER ALLOY, 30µ GOLD PLATED		
OPERATING TEMPERATURE:	-55°C ~ 125°C		
POWER/CO-AX CONTACT RATING:	30A (CURRENT)		


(IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE: $10m\Omega$ MAX. 5000MΩ min.

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE:


NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

1000V AC rms



COMBINATION D-SUB		SW REFERENCE NO.: 630 COMBO ASSEMBLY			
		DRAWN: C.B	DATE: JAN. 01/20	19	
		CHECKED:	DATE:		
EDAC INC TORONTO, ONTARIO CANADA YOUR CONNECTION TO QUALITY & SERVICE	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2	
		DRAWING NUMBER: 630-3W3-	-640-3N1	ISSUE	
		PART NUMBER: 630-3W3-	-640-3N1	1	



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY. COMPLIANT

