	10	9	8	7	6	5	4	3
F	NUMBER 1211930001 T(FINISHED LENGTH // +1.9 CM/-0 [1.0' +0.75"/- // +5.6 CM/-0 [3.3' +2.19"/-					
E								
D		.38 F	REF. [9.7]		0 WRAP	2.02 REF. [51.3] -	Ø.57 REF. [14.5]	
С	MECHANICAL				SHED LENGTH ———— 4.	00±1.00 [101.6±25.4] ——	b	T04
В	INSERT : BLAC COUPLING NU MOLDED BODY CABLE: 0.34mn WRAP LABEL: ELECTRICAL	T: NICKEL PLATED COPF Y: BLACK TPE n ² [22 AWG] 4 CONDUCT MYLAR YELLOW WITH B ING: 250V AC/DC	'ER ALLOY ORS BLACK JACKET		5/04/28 5/04/28 5/05/12	QUALITY GENERA SYMBOLS (UNLES	L TOLERANCES SS SPECIFIED)	0. DIMENSION STYLE INCH [MM]
A	ENVIRONMEN PROTECTION: OPERATION THE THE RECOMMI	ΓAL			INITIAL RELEASE INITIAL RELEASE EC NO: IPG2015-1880 EC NO: IPG2015-1880 CH'KD: VOU 2015/04/28 CH'KD: VOU 2015/04/28 APPR: BWOODMAN2015/05/12	NOLLANS V=0 4 PLACES 3 PLACES 2 PLACES 1 PLACE 1 PLACE ANG DRAFT WH MUS WITHIN	± ± KJOZ ± ± CHECK ± ± VOU ± ± APPRO ULAR ±.5° BWO	WIK 2014/02/13 ED BY DATE 2015/04/28 VED BY DATE ODMAN 2015/05/12
	10	9	8	7	6	5	4	3

