

Specification Sheet

Part Number: 596-00678



Solar Label, Reflective, Warning Photovoltaic Power Source, 6.5" x 1.0", V, Red, 10/pkg

Article Number	596-00678
Type	PVPSR10
Color	Red (RD)
Features & Benefits	<ul style="list-style-type: none">• Made with UV-stable inks and materials for durability and weather resistance.• Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.• Abrasion resistant for high-performance identification.• Meets NEC and IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.
Quantity Per	pack

Product Description

HellermannTyton makes it easier than ever for solar installers to meet PV labeling codes. Solar Label Convenience Packs allow installers to quickly and economically purchase high quality preprinted NEC 2014, 2017 and 2020 code-compliant solar installation labels. Packaged in 10-count quantities to meet the needs of smaller scale solar installations and independent contractors, Solar Label Convenience Packs are available in HellermannTyton's most popular preprinted NEC 2014, 2017 and 2020 code-compliant solar label formats. Each Solar Label Convenience Pack contains 10 solar installation labels. Choose from a variety of regular and reflective preprinted labels. For enhanced durability, clear laminate overlay labels are also available in a convenience pack.

Short Description

Solar Label, Reflective, Warning Photovoltaic Power Source, 6.5" x 1.0", V, Red, 10/pkg

Global Part Name

PVPSR10-505/281-RD

Technical Description

Pre-Printed Solar Label, 6.5" X 1", WARNING: PHOTOVOLTAIC POWER SOURCE, Red Reflective

Local Order Number 2

Cross Reference = 50 per roll: 596-00206

Width W (Imperial)

6.5

Width W (Metric)

165.1

Thickness T (Imperial)

0.0025

Thickness T (Metric)

64.0

Height H (Imperial)

1.0

Height H (Metric)

25.40

Width of Liner (Metric)

28.57

Width of Liner (imperial)

1.125

Material	Type 505/281, UV Stable Reflective Vinyl with Clear Polyester Laminate
Material Shortcut	505/281
Adhesive	Acrylic
Halogen free	No
Adhesive Operating Temperature	-40°F to +174°F (-40°C to +79°C)
Operating Temperature (Metric)	-40°F to +174°F (-40°C to +79°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Certification/Specification WEB	NEC2017 UL 969
Warranty (US)	Yes
UL Recognized (US)	Yes
Package Quantity(Imperial)	10
Package Quantity (Metric)	10
Customs Number	3919905060
Labels per Column	1

Labels per Row	1
Weight (Metric)	0.104
Weight (Imperial)	0.23