	ב בער בער בער בער בער בער בער בער בער בע	m D	0			
Image: state of the state	Linead					
CHARCTENTS     Subdraf:   Subject     Schell Material   Minimum     Schell Material   Schell Material     Schell Material   Schell Ma						
CHARACTERISTICS     -Standard: lased on MIL-DTI-38999 Series III     -Shell Material   :: Aluminium     -Shell Material   :: Aluminium     -Shell Material   :: Mickel     -insulator   :: Nickel     -insulator   :: Disminial     -Shell Material   ::: Mickel     -insulator   :: Disminial     Shell Material   ::: Mickel     -insulator   :: Disminial     Shell Material   ::: Mickel     -insulator   :: Disminial     Shell Material   ::: Mickel     -insulator   :: Contacts     -Seals & Grommet   :: Slicon Elastomer     -Contact Plaing   :: Gold Wore copper Alloy 0.8µm minimum     -Durability   ::: Stot Mating cycles     -Belvered without Souriau contacts   ::: Contact Plaing     -Temperature Range   ::: Gold Comperature     Mass   ::: 23.4 g :: 10%     Mass   ::: 23.4 g :: 10%     Mass   ::: Customet Ranking     Setter TYPE   :: Setter Marcel Comper Contact     Setter TYPE   :: Setter Marcel Comper Contact     Setter TYPE   :: Setter Marcel Cont			LAYOUT SF	OWN AS EXAMPLE		
Standard : Based on MIL-DTL-38999 Series III     Shell Material   :: Aluminitum     Shell Material   :: Comper Alloy     Sougas & Grommet   :: Slicon Elastomer     - Contact Plating   :: Gold over copper Alloy 8, minimum     - Durability   :: Sou Mating cycles     - Delevered without Souriau contacts   PN:: 8D513F088SCL     - Mass   :: 23.4 g ± 10%     Also S C SERIES:   8D 5     Basic SERIES:   8D 5     Shell Stress   : Delevered W/O Contacts     Shell Stress   : Delevered W/O Contacts     Shell Stress   : Delevered W/O Contacts     Shell Stress   : Soutact Plating Crimp Contact     Shell Stres   : Delevered W/O Contacts <td>Keying Shown as example</td> <td></td> <td></td> <td></td> <td></td> <td></td>	Keying Shown as example					
Shell Material   : Aluminium     Shell Material   :: Aluminium     Shell Material   :: Aluminium     Shell Material   :: Nickel     -Shell Plating   :: Nickel     -Contacts   :: Coper Alloy     -Seals & Grommet   : Silicon Elastomer     -Contact Plating   :: Sourial opper Alloy 0.8µm minimum     -Durability   : S00 diating cycles     -Delivered without Souriau contacts   -     -Temperature Range   : - 65°C to +200°C     -salt Spray   : 48 hours     -Mass   : 23.4 g ± 10%     Basic Series:   80     Shell Material   : S     CONTACT TYPE   : Stell TYPE     Shell Size List : 13   F     PLATING   : F     Platie   Control List     Control C trype : standard Crimp Contact   Sourial     Shell Size List : 13   Control T trype : standard Crimp Contact     Shell Size : 13   Control T trype : standard Cr	Connector					
-Contact Plating   ::::::::::::::::::::::::::::::::::::	-Shell Material : Aluminium ØS   -Shell Plating : Nickel Z   -Insulator : Thermoplastic	29.4 Max 31 Max	due to a use of the P the Specifications issued	roducts which does not compl by either of the Parties or by a	y with third party	
- Durability :: 500 Mating cycles - Delivered without Souriau contacts - Temperature Range :: -65°C to +200°C - Salt Spray :: 48 hours - Mass :: 23.4 g ± 10% BASIC SERIES: 8D 5 - 13 F 08 S C L SHELL TYPE :: Plug with RFI Shielding CONTACT TYPE :: Standard Crimp Contact SHELL SIZE :: 13 PLATING :: F = Nickel CONTACT TYPE :: SOURIAU COM SHELL SIZE :: 13 PLATING :: F = Nickel CONTACT LAYOUT ::13-08 CONTACT LAYOUT ::13-08 C						
-Salt Spray : 48 hours -Mass : 23.4 g ± 10% A 17-10-2016 First Release -Mass : 23.4 g ± 10% A 17-10-2016 First Release -Mass : 23.4 g ± 10% A 17-10-2016 First Release -Mass : 23.4 g ± 10% BASIC SERIES: 8D 5 - 13 F 08 S C L BASIC SERIES: 8D 5 - 13 F 08 S C L BASIC SERIES: 8D 5 - 13 F 08 S C L SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 13 PLATING : F = Nickel CONTACT TYPE : SOCKET(500 Matings) CONTACT TYPE : SOCKET(500 Matings) CONTAC	-Durability : 500 Mating cycles		PN: 8			
-Salt Spray : 48 hours -Mass : 23.4 g ± 10% -Mass : 23.4 g ± 10% BASIC SERIES: 8D 5 - 13 F 08 S C L SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 13 PLATING : F = Nickel CONTACT TYPE : SOCKET(500 Matings) CONTACT TYPE : Standard Crimp Contact Step reproduced or communicated without permission PLATING : F = Nickel CONTACT TYPE : SOURIAU DRG N° SHEET	-Temperature Range : -65°C to +200°C		17-10-2016 First Release			
BASIC SERIES:   8D   5   -   13   F   08   S   C   L     BASIC SERIES:   8D   5   -   13   F   08   S   C   L   C   Secure 4   S		ISS	DATE Latest modification - by	c		DD N°
BASIC SERIES.   BB SIC SERIES.   BB SIC SERIES.   BB SIC SERIES.   BI SIC				Aluminium Plug 8D series		
SHELL TYPE : Plug with RFI Shielding   Delivered W/O Contacts   NA   ±   859     CONTACT TYPE : Standard Crimp Contact   ORIENTATION : C   SOURIAU   This document is the property of SOURIAU.COM     SHELL SIZE : 13   CONTACT TYPE : SOCKET(500 Matings)   CONTACT LAYOUT : 13-08   FORMAT   SOURIAU DRG N°   SHEET	BASIC SERIES: 8D 5 - 13 F 08 S C L	SCAL			NPRDS / PROJECT	
CONTACT TYPE : Standard Crimp Contact   ORIENTATION : C   SOURIAU   SOURIAU   SOURIAU.COM   it must not be reproduced or communicated without permission     SHELL SIZE : 13   CONTACT TYPE : SOCKET(500 Matings)   CONTACT LAYOUT : 13-08   FORMAT   SOURIAU   SOURIAU   SOURIAU	SHELL TYPE : Plug with RFI Shielding	Delivered W/O Contacts NA				
PLATING : F = Nickel FORMAT SOURIAU DRG N° SHEET		500	N : C SOURIAU WWW.SOURIAU.COM it must not be reproduced or			
				JRIAU DRG N°		
	I		n		1	1/2

-	Ŧ	۵	г п	m		0
		Contact Layout				
4		$x \begin{pmatrix} g \\ g$				
		Contacts (Insert arrangement 13-8)       tact ibition     Contact location       X-axis     Y-axis (mm)       A     +.065 (1.65)     +.157 (3.99)       B     +.170 (4.32)     +.000 (0.00)       C     +.120 (3.05)    120 (3.05)       D    000 (0.00)    170 (4.32)       E    120 (3.05)    120 (3.05)       F    170 (4.32)     +.000 (0.00)       G    065 (1.65)     +.157 (3.99)       H     +.000 (0.00)     +.044 (1.12)				
ယ	Shell Arrangement Nu size no. co 13 -8	Imber of Size Service Contact Supersed ontacts contacts rating location 8 20 I All MS20051				
	-					SOURIAU shall not be liable for an due to a use of the Products wi the Specifications issued by either o (professional recommenda
N						Counti FR PN: 8D513F
					A 17-10-20 ISS DATE Designed By:	16 First Release Latest modification - by Date:
					SCALE	Alumin General linear
<u> </u>					SOURIA	U WWW.SOURIAU.C
					FORMAT A3	SOURIAU 8D513F0
L	Н	G	F	E	D	C

			4
			3
any non-conformi which does not co r of the Parties or I dation, technical n ntry Jurisc R BFO8SCL	mply with by a third party		2
	CUSTOMER DRAWING	MOD N°	-
iinium Plug 8	D series		
r	NPRDS / PROJECT <b>859</b>		
.COM	This document is the prop SOURIAU it must not be reproduc communicated without pe	ed or	
U DRG N° F08SCL-C		SHEET 2/2	
B	A		1

ω

A