	T Q T	m	D	0	B		_
4	R 22.6 Max () () () () () () () () () () () () ()	S		<image/> <image/>	MPLE		4
	Keying Sh CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III	own as example Connector dimension Dim Nominal					
N	-Shell Material: Aluminium-Shell Plating: Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer-Contact Plating: Gold over copper Alloy 0.8μm minimum	A 38.1±0.3 B 23.82+0.1/-0.15 R 32.5Max S 34.9±0.4 W 2.2+0.9/-0.1 VV THREAD M18x1-6g		SOURIAU shall not be liable for any r due to a use of the Products whic the Specifications issued by either of tl (professional recommendatio Country FR	h does not comply with ne Parties or by a third party		2
	-Durability: 500 Mating cycles-Delivered without Souriau contacts-Temperature Range: -65°C to +200°C-Salt Spray: 48 hours		A 28-09-201	PN: 8D713F0	4PDL		-
	-Mass : 22.9 g ± 10%		ISS DATE Designed By: TITLE	Latest modification - by Date: Aluminium	customer drawing Receptacle 8D series	MOD N°	-
-	BASIC SERIES: 8D 7 - 13 F 04 P D SHELL TYPE : Jam nut Receptacle - - 13 F 04 P 04 CONTACT TYPE : Standard Crimp Contact - <td< td=""><td>Delivered W/O Contacts ORIENTATION : D</td><td>SCALE NA SOURIAL</td><td>General linear Tolerances: ±</td><td>NPRDS / PROJECT 859 This document is the pro SOURIAU</td><td></td><td>1</td></td<>	Delivered W/O Contacts ORIENTATION : D	SCALE NA SOURIAL	General linear Tolerances: ±	NPRDS / PROJECT 859 This document is the pro SOURIAU		1
	SHELL SIZE : 13 PLATING : F = Nickel	CONTACT TYPE : PIN(500 Matings) CONTACT LAYOUT : 13-04	FORMAT A3	SOURIAU I 8D713F04	DRG N° PDL-C		
	H G F		D	C	B A		

ſ	т <u>О</u> т	
4	Contact Layout $ \underbrace{\begin{array}{c} & & & \\ & & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & & \\ & & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & $	Panel cutout JAM NUT RECEPTACLE (TYPE 7)
	Contacts (Insert arrangement 13-4) Location Contact position ID Contact (mm) Supersedes (contact Supersedes (contact Supersedes Shell Arrangement (no. Number of (contact Size Supersedes (contact Supersedes Supersedes <td></td>	
c.s	size no. contacts contacts rating location 13 -4 4 16 I Ali MS20051-4	Dim Nominal B 24.26+0/-0.25 ØC 25.65+0.25/-0
		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)
2		Country Jurisdiction & Control List 2 FR Not Listed 2 PN: 8D713F04PDL 2
		A 28-09-2016 First Release MOD N° ISS DATE Latest modification - by MOD N° Designed By: Date: CUSTOMER DRAWING TITLE Aluminium Receptacle 8D series
		SCALE General linear NPRDS / PROJECT NA Image: Main recorpt and the property of sources 859 SOURIAU WWW.SOURIAU.COM SOURIAU it must not be reproduced or
	H G F E	Format SOURIAU DRG N° A3FORMAT A3SOURIAU DRG N° 8D713F04PDL-CSHEET 2/2DCBA