

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

2015

LOC

DIST

REVISIONS

© COPYRIGHT 2015 BY TE CONNECTIVITY

ALL RIGHTS RESERVED.

P	LTR	DESCRIPTION	DATE	DWN	APVD
	1	NEW DEVELOPMENTAL RELEASE	12JAN2015	JA	DM
	2	REVISED PER ECO-15-004372	19MAR2015	JA	DM
	A	PRODUCTION RELEASE PER ECO-15-014220	01OCT2015	JA	DM
	A1	REVISED PER PCN :E-18-011823	23JUL2018	DD	DM

Ø6.90
[.272]

Ø15.80
[.622]

15.00
[.591]

SCALE 4:1

TE INTERNAL PN	DEUTSCH PN	WIRE SEALING RANGE
2289241-1	WS-25-001	8.17-9.66 [.322-.380]

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN 12JAN2015

CHK JAIME C. APOSTOL

12JAN2015

APVD DENNIS WHITACRE

12JAN2015

DAVID MEYER

PRODUCT SPEC

108-151027

APPLICATION SPEC

114-151028

WEIGHT

1.88g

STE TE Connectivity

NAME
WIRE SEAL, 25mm²
SEAL RANGE - 8.17mm-9.66mm
Ø8mm CONTACT

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	4AFU8	WS-25-001	-

CUSTOMER DRAWING	SCALE	SHEET	OF	REV
	7:1	1	1	A1

DIMENSIONS:
mm [INCHES]TOLERANCES UNLESS
OTHERWISE SPECIFIED:

0 PLC	±
1 PLC	±
2 PLC	±0.64 [.025]
3 PLC	±
4 PLC	±
ANGLES	±0°30'0"

MATERIAL

FINISH

△ 2 MATERIAL: SILICONE (VMQ), COLOR: BLUE.

1. PART IS USED ON RECEPTACLE DTSK04-1-08PX AND PLUG DTSK06-1-08SX. (X = A,B,C KEYS)

NOTES: UNLESS OTHERWISE SPECIFIED

1470-19 (3/11)