


**TECHNICAL SPECIFICATIONS**

**D-Sub Hood:**

Material: UL 94 V-0 Plastic Material  
 Operating Temperature: -55°C to +110°C  
 Cable Entry: Side  
 Thumbscrews: UNC 4-40 (Standard)  
 Cable O.D.: Up to 11,5mm  
 Colour: Black

**Male Sub-D Connector:**

Insulator: PBT, Black, UL94 V-0  
 Shell: Steel, Tin Plated  
 Contact pins: Copper Alloy  
 Stamped & Formed Pins: Class 3, 100 inserts min.  
 Machined Contact Pins: Class 1, 500 inserts min.  
 Contact Plating: Selective Gold over Nickel  
 Operating Temperature: -55°C to +105°C  
 Withstanding voltage: 1000V for 1 minute  
 Insulator resistance: 1000MΩ min.



Size D45PK-P	Dim A	Dim B	Dim C
9-way	31,0	36,3	15,0
15-way	39,5	40,3	15,0
25-way	53,2	40,3	15,0
37-way	69,7	40,3	15,0

**Features:**

- Available in sizes 9-15-25-37
- Suitable for any common Sub-D connector
- Strain relief inserts ensure a secure termination
- Re-openable

**Ordering information - Black Insulator:**

Size:	P/N - Kitted:	Class 3 - 100 inserts min.
9-way	6355-0034-01	D45PK-P-09-DBP-K
15-way	6355-0034-02	D45PK-P-15-DBP-K
25-way	6355-0034-03	D45PK-P-25-DBP-K
37-way	6355-0034-04	D45PK-P-37-DBP-K

Size:	P/N - Kitted:	Class 1 - 500 inserts min.
9-way	6355-0035-01	D45PK-P-09-DMP-K
15-way	6355-0035-02	D45PK-P-15-DMP-K
25-way	6355-0035-03	D45PK-P-25-DMP-K
37-way	6355-0035-04	D45PK-P-37-DMP-K

**Ordering information - White Insulator:**

Size:	P/N - Kitted:	Class 3 - 100 inserts min.
9-way	6355-8034-01	D45PK-P-09-DBP-W-K
15-way	6355-8034-02	D45PK-P-15-DBP-W-K
25-way	6355-8034-03	D45PK-P-25-DBP-W-K
37-way	6355-8034-04	D45PK-P-37-DBP-W-K

Size:	P/N - Kitted:	Class 1 - 500 inserts min.
9-way	6355-8035-01	D45PK-P-09-DMP-W-K
15-way	6355-8035-02	D45PK-P-15-DMP-W-K
25-way	6355-8035-03	D45PK-P-25-DMP-W-K
37-way	6355-8035-04	D45PK-P-37-DMP-W-K

