

13162000	DATA SHEET	
Valid from: 17.09.2018	EPIC® H-D 1.6 Machined Contacts	

Description

- For inserts and modules of the EPIC® rectangular connectors



Article-Number	Article	Version	Conductor cross-section (mm ²)	cross-section ratio	Surface	Stripping length (mm)
Contact						
13162000	H-D 1,6 machined	male	0,14 - 0,37	1	Ag	8,0
13163000	H-D 1,6 machined	female	0,14 - 0,37	1	Ag	8,0
13162100	H-D 1,6 machined	male	0,5	2	Ag	8,0
13163100	H-D 1,6 machined	female	0,5	2	Ag	8,0
13162200	H-D 1,6 machined	male	0,75 - 1	3	Ag	8,0
13163200	H-D 1,6 machined	female	0,75 - 1	3	Ag	8,0
13162300	H-D 1,6 machined	male	1,5	4	Ag	8,0
13163300	H-D 1,6 machined	female	1,5	4	Ag	8,0
13162400	H-D 1,6 machined	male	2,5	5	Ag	5,8
13163400	H-D 1,6 machined	female	2,5	5	Ag	5,8
13162500	H-D 1,6 machined	male	0,14 - 0,37	1	Au	8,0
13163500	H-D 1,6 machined	female	0,14 - 0,37	1	Au	8,0
13162600	H-D 1,6 machined	male	0,5	2	Au	8,0
13163600	H-D 1,6 machined	female	0,5	2	Au	8,0
13162700	H-D 1,6 machined	male	0,75 - 1	3	Au	8,0
13163700	H-D 1,6 machined	female	0,75 - 1	3	Au	8,0
13162800	H-D 1,6 machined	male	1,5	4	Au	8,0
13163800	H-D 1,6 machined	female	1,5	4	Au	8,0
13162900	H-D 1,6 machined	male	2,5	5	Au	5,8
13163900	H-D 1,6 machined	female	2,5	5	Au	5,8



Remark

Photographs are not to scale and do not represent detailed images of the respective products.

Creator: MANA2/PDP Released: IVSE1/PDP	Document: DB13162000EN Version: 01	Page 1 of 1
---	---------------------------------------	-------------