

# GMA.1B.065.DN

## SUMMARY

#### # Wires



Image is for illustrative purpose only

Series	1B		
Termination type	No contacts / Accessory		
IP rating	0		
AWG wire size	0.00 - 0.00		
Cable Ø	6.50 - 7.00 mm		
Status	active		

#### Download

Request a quote Catalog

# **TECHNICAL DETAILS**

#### **Mechanics**

Shell Style/Model	GMA*: Bend relief Black
Keying	No keying
Housing Material	Thermoplastic polyurethane elastomer (Elastollan 1185 A)
Variant	N : Black
Weight	.97 g
Performance	


Configuration Insulator Rated Current

#### Others

Temp (min / max): -40°C / +80°C

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

### DRAWINGS



No keying

#### Dimensions

	А	L
mm.	6.5	30
in.	0,26	1,18

### **RECOMMENDED BY LEMO**

#### Tools

#### Cables

150222		

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.