


Date	SYM	REVISION RECORD	AUTH	DR.	CK.
4/15/06	A	ADDED "ROHS COMPLIANT" UPDATED MATERIAL NOTE	T.B.	B.S.	
03/29/13	B	UPDATED TO "ROHS 2 COMPLIANT"	T.B.	B.S.	
06/14/13	C	UPDATED TITLE	T.B.	B.S.	
07/07/17	D	DIM. 5.0 WAS 3.18 DIM. 150.0 WAS 152.4	T.B.	B.S.	
07/17/17	E	ADDED MOUNTING INSTRUCTION	T.B.	B.S.	

Mounting Instruction:
Use 4-40 machine screwst.
also adhesives and double sided tapes work well.

NOTES:

1. MATERIAL:

- HOUSING : BLACK POLYPROPYLENE, PP-1040
- FLAMMABILITY RATING -UL94-HB, UL FILE NO. E216959
- TEMPERATURE RANGE: -10°C to +100°C
- RIVETS: BRASS, NICKEL PLATED.
- SPRING: SPRING STEEL, NICKEL PLATED.
- WIRE: 26AWG, UL1007, CSA, TR64, 300V, 80°C
- CONTACT RESISTANCE: UNDER 50mΩ FOR +/- CONTACTS PER EIA-540J000
- ROHS 2 COMPLIANT

Tolerance (Except as noted)	 Memory Protection Devices, Inc 200 Broad Hollow Road, Farmingdale, New York 11735	Scale	Drawn By B.S.
			Approved By T.B.
decimal ±.5 (.020)	Title EIGHT "AAA" CELL HOLDER WITH WIRE LEADS		
Fractional ± .8 (.030)		Date 07/17/17	Drawing Number BH28AAAW
Angular ± 3°			