






APPROVED: _____
 DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	1/26/21	



BUTTON POSITION		
FUNCTION	ON	ON
TERMINALS	2-3, 5-6	2-1, 5-4

SPECIFICATIONS:

Material:
 Case: DAP, Rated UL94V-0
 Plunger: Brass, color Black w/ O-Ring
 Bushing: Brass, color Black w/ O-Ring
 Movable Contact: Copper Alloy, Silver Plated
 Terminal: Copper Alloy, Silver Plated
 Electrical:
 Rating: 6A @ 125VAC or 28V DC
 3A @ 250VAC
 Contact resistance: 10 mΩ max
 Insulation resistance: 1,000 Mohms min
 Dielectric withstanding voltage: 1,500V RMS @Sea level
 Life: 50,000 cycles at full load
 Temperature Rating:
 Operating temperature: -30°C to +85°C
 Environmental:
 Sealed IP68 Rated
 Lead free, RoHS compliant



UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM] TOLERANCES: EXCEPT AS NOTED INCHES HOLES .X ± .10 Ø.X ± .10 .XX ± .020 Ø.XX ± .015 .XXX ± .015 Ø.XXX ± .010		ADAM TECH 909 Rahway Avenue, Union, NJ 07083 Phone: 908-687-5000 Fax: 908-687-5710	
APPROVALS DRAWN LH CHECKED AC APPROVED		DATE 1/26/21 1/26/21	
TITLE HIGH PERFORMANCE PUSH BUTTON SWITCH, DPDT, ON-ON, SILVER PLATED, SOLDER TYPE		SIZE X	PART NO. SW-PB10-BAA1QE-4
REF: S00198T		SCALE: NTS	SHEET 1 OF 1