



TECHNICAL

LISTED: cULus

RATED SUPPLY VOLTAGE: 120 VAC

RATED CURRENT: UP TO 20 AMPS

RESET TYPE: MANUAL

OPERATING FREQUENCY: 60 Hz

TYPE: CLASS A

GROUND TRIP CURRENT: 4-6 mA

OVERLOAD CURRENT: 120 AMP

INSULATION VOLTAGE: 1,500 VRMS - 1 MINUTE

ENDURANCE OPERATIONS: 3000 OPERATIONS

ENCLOSURE: NEMA 3R

MATERIAL NO.	ENGINEERING NO.	LENGTH "A"	LENGTH "L"
1301530122	20052-1	9.50 IN.	1 FT. 11.4 IN
1301530127	20052-25	23 FT. 10.5 IN.	25 FT. 0.4 IN.
1301530131	20052-6	4 FT. 10.5 IN.	6 FT. 0.4 IN.

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

DIMENSION UNITS	SCALE	CURRENT REV DESC: REMOVED OBSOLETE PART NUMBER AS PER PCN#511695.	molex		
INCH	NTS				
GENERAL TOLERANCES (UNLESS SPECIFIED)			GFCI INLINE 20A, 120V ATTACHABLE W/PLUG & CONN. WATERTITE		
ANGULAR TOL	± °		PRODUCT CUSTOMER DRAWING		
4 PLACES	±		DOCUMENT NUMBER		
3 PLACES	±		1301530122		
2 PLACES	±		DOC TYPE		
1 PLACE	±		PSD		
0 PLACES	±		DOC PART		
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			REVISION		
THIRD ANGLE PROJECTION			A1		
DRAWING			MATERIAL NUMBER		
D-SIZE			SEE TABLE		
SERIES			CUSTOMER		
130153			GENERAL MARKET		
SHEET NUMBER			1 OF 1		