

Revised 10 June 2011

Printed 10 Jun 2011

WELLER WB1 2oz.- BUTANE FUEL

MATERIAL IDENTIFICATION

Marketer: Cooper Tool Co./ Weller
1000 Lufkin Rd.
Apex, NC 27539

Phone Number: 919-387-0099
Transportation Emergency: CHEMTREC 800-424-9300

Chemical Trade Name,
synonyms: A-28

Chemical Family: Petroleum Hydrocarbon, LP Gas

Chemical Formula: mixture

Hazard Ratings:

4 = Extreme Health = 1
3 = High Fire = 4
2 = Moderate Reactivity = 0
1 = Slight
0 = Insignificant

COMPONENTS

Material	CAS Number	PEL/TLV, Source	Percent
Isobutane (volume)	75-28-5	1000 ppm, OSHA	80
n-butane (volume)	106-97-8	1000 ppm, OSHA	20

PHYSICAL DATA

Boiling Point	15.5-31.1°F
Pressure in can at 70°F	35 - 50 psig
Vapor Density (Air=1)	Greater than 2.0
Solubility in water	Less than 0.1% By Weight @ 70°F
Specific Gravity (Water=1)	0.5676
Percent Volatile by weight	100%
Evaporation Rate (BuAce=1)	Gas
Appearance and odor	Liquefied compressed gas, flash evaporates at room temperature when released from can, colorless gas with strong mercaptan (skunk-like) odor due to stenching agent added to gas for leak detection purposes.

HAZARDOUS REACTIVITY

Stability	Stable
Conditions to avoid	Contact with sparks, open flame or any source of ignition.
Hazardous Polymerization	Will not occur
Hazardous Decomposition Products	May produce carbon monoxide when oxidized with a deficiency of oxygen.

FIRE AND EXPLOSION DATA

Flammability Category	Extremely Flammable (Reference - Consumer Product Commission, flame projection test for aerosol products, per 16 CFR 1500.45)
Flash Point	Less than -117°F
Flammable Limits	LEL% 1.8 UEL% 8.4
Extinguishing Media	If feasible, stop flow of gas. Use water to cool fire-exposed cans, surroundings and to protect personnel working on shut off. Water spray, dry powder or carbon dioxide can be directed at flame area, if gas flow cannot be stopped, to reduce fire intensity. DO NOT COMPLETELY EXTINGUISH FLAME UNLESS GAS FLOW IS SHUT OFF!
Unusual Fire and Explosion Hazards	Avoid possible bursting of aerosol can. Do not store where temperature may exceed 120°F. Do not puncture or incinerate.
Special Fire Fighting Procedures	Avoid possible accumulations of vapors at floor level, as vapor is heavier than air. Self-contained breathing apparatus and protective clothing should be worn in fighting fires involving chemicals. This product is extremely flammable at all times. Keep away from any sources of inadvertent ignition, including heat, fire, sparks, or flame.

HEALTH HAZARD INFORMATION

Suggested Exposure Guideline	1000 ppm
Primary Route of Exposure	Inhalation, skin contact
Inhalation	This product is an asphyxiate and may exhibit anesthetic properties at very high concentrations. Initial symptoms of exposure at these concentrations are disorientation, lack of coordination, rapid respiration, headache, and nausea. Continued exposure may result in unconsciousness, coma, and possible death.
Skin Contact	Contact with liquefied gas or gas under pressure may cause skin burns and frostbite.
Eye Contact	The gas phase is not expected to cause eye irritation. However, the liquid can cause frostbite and burns. This hazard evaluation is based on the data from similar materials.

Carcinogenicity None of the components in this material are listed by IARC, NTP, OSHA, or ACGIH as a carcinogen.

FIRST AID

Inhalation Remove to fresh air. Artificial respiration, consult physician.

Skin Contact Treat burned or frostbitten skin by flushing or immersing affected areas in lukewarm water. If skin is not burned, keep warm and stimulate circulation with massage. Seek immediate medical attention.

Eye Contact Flush eyes well with running water for 15 minutes.

Ingestion NA, product is gaseous at normal temperature and pressure.

SPILL OR LEAK PROCEDURES

Steps to be taken in case material is released or spilled Protect from any ignition source, keep away from heat, fire, sparks, or flame. Ventilate area well. Avoid accumulation of vapor at low levels.

Waste disposal method Dispose of in accordance with all local, state and federal regulations. Do not puncture or incinerate.

SPECIAL PROTECTION INFORMATION

Respiration Protection If TLV is exceeded wear NIOSH-approved self-contained breathing device or respirator.

Ventilation Must be adequate to maintain vapors at less than 800 ppm, particularly at floor level as vapors are heavier than air.

Protective gloves None needed for normal use. Solvent-resistant rubber type recommended if prolonged exposure expected.

Eye Protection Safety glasses or goggles recommended

HANDLING AND STORAGE PRECAUTIONS

Precautions to be taken in handling and storage Do not store where temperature may exceed 120°F. Store away from, fire, sparks, or flame. Store in suitable area for hazardous materials storage.

D.O.T. Shipping Classification Liquified petroleum gas 2.1

Hazard Class 2.1

ID Number

UN1075

TSCA Statement: All the components of this product are in compliance with the Toxic Substances Control Act (TSCA) and are either listed on the TSCA Inventory or otherwise exempted from listing.

SPECIAL PRECAUTIONS

Precautions for usage

Do not use near heat, fire, flame or sparks. Avoid excessive breathing of vapor. Do not spray in direction of body. Use only in accordance with directions.

Notice: This data represents typical values, not product specifications. No guarantee of accuracy or completeness is made. No responsibility is assumed for any kind of loss or damages arising from use of this data.

End of MSDS