

## Specification Sheet

Part Number: 151-00785



Connector Clip w/Fir Tree, 0.7 - 4.0 mm Panel Thickness, 6.0 - 6.7 mm Hole Dia, PA66HIRHS, Black, 5000/box

**Article Number**

151-00785

**Type**

CCFT6LG

**Color**

Black (BK)

**Features & Benefits**

- Head design contains clamping rails to provide full circumferential compression around bundles.
- Bent tail allows for quick insertion into head.

**Quantity Per**

bag

**Product Description**

Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

|  |  |
|--|--|
| <b>Short Description</b>                       | Connector Clip w/Fir Tree, 0.7 - 4.0 mm Panel Thickness, 6.0 - 6.7 mm Hole Dia, PA66HIRHS, Black, 5000/box |
| <b>Global Part Name</b>                        | CCFT6LG-PA66HIRHS-BK   |
| <b>Technical Description</b>                   | Connector Clip, Black  |
| <b>Fixation Method</b>                         | Fir Tree   |
| <b>Panel Thickness Min(Imperial)</b>           | 0.028  |
| <b>Panel Thickness Max(Imperial)</b>           | 0.16   |
| <b>Panel Thickness Min (Metric)</b>            | 0.7  |
| <b>Panel Thickness Max (Metric)</b>            | 4.0  |
| <b>Mounting Hole Diameter D (Imperial)</b>     | 0.24 - 0.26  |
| <b>Mounting Hole Diameter D (Metric)</b>       | 6.0 - 6.7 mm   |
| <b>Mounting Hole Diameter D Min (Imperial)</b> | 0.24   |
| <b>Mounting Hole Diameter D Max (Imperial)</b> | 0.26   |
| <b>Mounting Hole Diameter D Max (Metric)</b>   | 6.7  |
| <b>Material</b>                                | Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)   |
| <b>Material Shortcut</b>                       | PA66HIRHS  |

|                                       |                                   |
|---------------------------------------|-----------------------------------|
| <b>Flammability</b>                   | UL 94 HB                          |
| <b>Operating Temperature (Metric)</b> | -40°F to +221°F (-40°C to +105°C) |
| <b>Reach Complaint(Article 33)</b>    | Yes                               |
| <b>ROHS Complaint</b>                 | Yes                               |
| <b>Package Quantity(Imperial)</b>     | 5000                              |
| <b>Package Quantity (Metric)</b>      | 5000                              |
| <b>Customs Number</b>                 | 3926909988                        |
| <b>Content Unit(BMEcat)</b>           | pcs.                              |
| <b>Weight (Metric)</b>                | 0.8                               |