



Material
 Terminal body
 (contact pin): Brass(CuZn) Tin plated
 Insulator (housing): Thermoplastic (UL94V-0),Green

Electrical cULus/CSA/VDE
 Voltage rating: 300VAC/300VAC/300VAC
 Current rating: 20A/20A/20A
 Wire range:
 Solid wire(AWG):
 Stranded wire(AWG):
 Withstanding Voltage: 1.6KV/2.5KV/2.5KV
 Operating temperature: -30°C to +105°C
 Soldering temperature: 250°C±10°C/5 Sec
 Safety Approval:

N= NUMBER OF CONTACTS

RoHS compliant

Unit: mm



File No.: E349947

Scale	1:1					Date	Name	Customer-No.
TOLERANCE						Drawn	10.12.2009	Dean
X.	±0.50					Approved	18.04.2016	Joanna
X.X	±0.30							
X.XX	±0.10							
DIM	TOL	②	Add UL	18.04.2016	Joanna	ASSMANN WSW-No.		A-TB500-OQxxCV
X.°	±1°	①	Drawn	10.12.2009	Dean	Drawing-No.		
Angle	TOL	Id.	Modification	Date	Name	ASSMANN WSW/ components		ASS 3861 CO rev02
						Replace		Sheet



ASS 3861 CO rev02

Replace Sheet