

**LINEAR TECHNOLOGY MATERIALS DECLARATION**

ltc2636cms-hmi10#trpbf

(Engineering Calculation)

MSOP

(printed on: 2020-07-11 22:01:05)

**TOTAL MASS (g) : 0.037693**

COMPONENT MATERIAL	VENDOR/ INDUSTRY NAMES	CONSTITUENT NAME	CAS NUMBER	CONSTITUENT MASS (g)	CONSTITUENT (PPM) OF MATERIAL	CONSTITUENT (PPM) OF TOTAL PKG.		
Active Device	Linear Technology	Silicon (Si)	7440-21-3	0.002628	1000000	69721.125		
Die Coat	Dow Corning	Silicone	69430-27-9	0.000000	0	0		
Lead Frame	Cu	Copper (Cu)	7440-50-8	0.013845	975000	367309.375		
		Iron (Fe)	7439-89-6	0.000355	25000	9418.18847656		
		Phosphorus (P)	7723-14-0	0.000004	300	106.120429993		
		Zinc (Zn)	7440-66-6	0.000010	700	265.301086426		
		Nickel (Ni)	7440-02-0	0.000000	0	0		
		Silicon (Si)	7440-21-3	0.000000	0	0		
		Magnesium (Mg)	7439-95-4	0.000000	0	0		
		Tin (Sn)	7440-31-5	0.000000	0	0		
<b>Lead Frame Total:</b>				<b>0.014214</b>	<b>1001000</b>	<b>377098.9375</b>		
Plating	PMI	Exter. Plating Pb	7439-92-1	0.000000	0	0		
		Exter. Plating Sn	7440-31-5	0.000710	1000000	18837.0390625		
		<b>External Plating Total:</b>				<b>0.000710</b>	<b>1000000</b>	<b>18837.0390625</b>
		Inter. Plating Ni	7440-02-0	0.000000	0	0		
		Inter. Plating Ag	7440-22-4	0.000086	1000000	2281.58911133		
<b>Internal Plating Total:</b>				<b>0.000086</b>	<b>1000000</b>	<b>2281.58911133</b>		
Die Attach	ELECTRICALLY CONDUCTIVE ADHESIVE	Silver (Ag)	7440-22-4	0.000836	750000	22179.171875		
		Tin (Sn)	7440-31-5	0.000000	0	0		
		Lead (Pb)	7439-92-1	0.000000	0	0		
		Silica (SiO2)	60676-86-0	0.000000	0	0		
		Indium (In)	7440-74-6	0.000000	0	0		
		Metal Oxide		0.000000	0	0		
		Antimony (Sb)	7440-36-0	0.000000	0	0		
		Resin (EP)		0.000279	250000	7401.90039062		
<b>Die Attach Total:</b>				<b>0.001115</b>	<b>1000000</b>	<b>29581.0703125</b>		
Encapsulation	MULTI-AROMATIC RESIN Br/Sb FREE	Resin (EP)		0.002439	130000	64706.9296875		
		Bromine (Br)	40039-93-8	0.000000	0	0		
		Silica (SiO2)	60676-86-0	0.015571	830000	413100.34375		
		Antimony Trioxide (Sb2O3)	1309-64-4	0.000000	0	0		
		Metal Hydroxide		0.000657	35000	17430.28125		
		Carbon Black (C)	1333-86-4	0.000094	5000	2493.83007812		
		<b>Encapsulation Total:</b>				<b>0.018761</b>	<b>1000000</b>	<b>497731.34375</b>
Bond Wire Estimated	AFW/TANAKA/ Kn	Gold (Au)	7440-57-5	0.000179	1000000	4748.88916016		
					<b>TOTAL MASS (g) :</b>	<b>0.037693</b>		