

## NOTES:

MATERIAL:	
HOUSING:	
SHELL:	
CONTACT:	
CONTACT.	

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, GOLD FLASH PLATED

OPERATING TEMPERATURE:

WITHSTANDING VOLTAGE:


.XX ±0.13

.XXX ±0.05


POWER/CO-AX CONTACT RATING:30A (CURRENT)(IF PRESENT)SIGNAL CONTACT CURRENT RATING:5A PER CONTACTSIGNAL CONTACT RESISTANCE:10mΩ MAX.INSULATOR RESISTANCE:5000MΩ min.DIELECTRIC5000MΩ min.

1000V AC rms

-55°C ~ 125°C



		SW REFERENCE NO.: 630 COMBO ASSEMBLY				
			COMBINATION D-SUB DRAWN: C.B		DATE: JAN. 01/2019	
			CHECKED:	DATE:		
	EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2	
	TORONTO, ONTARIO CANADA	SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DRAWING NUMBER: 630-5W5	-250-3TA	ISSUE	
YOUR CONNECTION	YOUR CONNECTION TO QUALITY & SERVICE		PART NUMBER: 630-5W5	-250-3TA	1	





THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

