



4 Type

- A 2x2 tapped insert
- C 2x2 bores for countersunk screw
- D 2x2 threaded stud

Metric table

1 l ₁	2 l ₂	3 d ₁ Tapped insert Threaded stud Type A, D		3 d ₂ Bore Type C	d ₃	h ₁	h ₂	h ₃	l ₃	l ₄	m ₁ ±0.2	m ₂ ±0.2	t
40 1.57	40 1.57	-	-	B 4.2	4 0.16	16.5 0.65	10 0.39	11.5 0.45	-	14 0.55	25.5 1.00	25.5 1.00	-
48 1.89	48.1 1.89	M 5	M 6	B 5.5	5 0.20	20.5 0.81	12.5 0.49	14.5 0.57	15 0.59	17 0.67	31 1.22	30 1.18	11 0.43
65 2.56	64.9 2.56	M 6	-	B 6.5	6 0.24	25 0.98	14 0.55	17 0.67	20 0.79	24 0.94	40 1.57	40 1.57	11 0.43
98 3.86	97.8 3.85	M 10	-	B 10.5	8 0.31	37 1.46	21 0.83	25 0.98	20 0.79	35 1.38	63 2.48	60 2.36	11 0.43

Dimensions in: millimeters - inches

Specification

- Body
 - Glass fiber reinforced
 - Black, matte finish
- Pin
 - Stainless steel
 - European Standard No. 1.4305 (AISI 303)
- Threaded stud
 - Steel, zinc plated, molded-in
- Tapped insert
 - Brass, molded-in
- RoHS compliant

Information

An economical, yet very durable, substitute for metal hinges.

see also...

- Hinges EN 151
- Lockable Hinges EN 151.2
- Hinges EN 151.3 (Technopolymer Plastic)
- Hinges EN 151.4 (Technopolymer Plastic)

How to order

1 **2** **3** **4**
C-40-40-B4.2-C

- | | |
|----------|--|
| 1 | Width l ₁ |
| 2 | Length l ₂ |
| 3 | Thread (Bore) d ₁ (d ₂) |
| 4 | Type |

3.1
3.2
3.3
3.4
3.5
3.6
3.7
3.8
3.9
3.10

