

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO J.S.T. AND SHALL NOT BE USED OR SHOWN WITHOUT WRITTEN PERMISSION.

4		3		2		1																											
ITEM	CONNECTOR PART NO.	DESCRIPTION	IPI CHECK	EOR CHECK	Applicable Tooling																												
1	SRSF-61-250A	RSF CONTACT, BRASS			APPLICATOR																												
2	UL1015, 16 AWG	BLACK			<table border="1"> <thead> <tr> <th colspan="2">Applicable Housings</th> </tr> <tr> <th>NO. OF CIRCUITS</th> <th>KEYLESS HOUSING PART NO.</th> </tr> </thead> <tbody> <tr><td>2</td><td>RSFP-2V-00</td></tr> <tr><td>3</td><td>RSFP-3V-00</td></tr> <tr><td>4</td><td>RSFP-4V-00</td></tr> <tr><td>5</td><td>RSFP-5V-00</td></tr> <tr><td>6</td><td>RSFP-6V-00</td></tr> <tr><td>7</td><td>RSFP-7V-00</td></tr> <tr><td>8</td><td>RSFP-8V-00</td></tr> <tr><td>9</td><td>RSFP-9V-00</td></tr> <tr><td>10</td><td>RSFP-10V-00</td></tr> <tr><td>11</td><td>RSFP-11V-00</td></tr> <tr><td>12</td><td>RSFP-12V-00</td></tr> </tbody> </table> <p>Other housings and configurations are available. Please contact JST for details.</p>			Applicable Housings		NO. OF CIRCUITS	KEYLESS HOUSING PART NO.	2	RSFP-2V-00	3	RSFP-3V-00	4	RSFP-4V-00	5	RSFP-5V-00	6	RSFP-6V-00	7	RSFP-7V-00	8	RSFP-8V-00	9	RSFP-9V-00	10	RSFP-10V-00	11	RSFP-11V-00	12	RSFP-12V-00
Applicable Housings																																	
NO. OF CIRCUITS	KEYLESS HOUSING PART NO.																																
2	RSFP-2V-00																																
3	RSFP-3V-00																																
4	RSFP-4V-00																																
5	RSFP-5V-00																																
6	RSFP-6V-00																																
7	RSFP-7V-00																																
8	RSFP-8V-00																																
9	RSFP-9V-00																																
10	RSFP-10V-00																																
11	RSFP-11V-00																																
12	RSFP-12V-00																																
<p>SUGGESTED MATING TAB NO SCALE</p> <table border="1"> <thead> <tr> <th></th> <th>WITHOUT STABILIZER</th> <th>WITH STABILIZER</th> </tr> </thead> <tbody> <tr> <td>DIM. "A"</td> <td>2.20 [0.087] MIN.</td> <td>4.20±0.15 [0.165±0.006]</td> </tr> <tr> <td>DIM. "B"</td> <td>7.40 [0.291] MIN.</td> <td>7.98 [0.314] MIN.</td> </tr> <tr> <td>DIM. "C"</td> <td>5.90 [0.232] MAX.</td> <td>(7.6)</td> </tr> </tbody> </table> <p>DIM. "A" → 8.00±0.15 [0.315±0.006] 3.40±0.10 [0.134±0.004] DIM. "A" → 1.00±0.10 [0.039±0.004] 2X DIM. "B" → 1.00±0.10 [0.039±0.004] 2X DIM. "B" → 6.35±0.10 [0.250±0.004] WITH STABILIZER DIM. "C" → #1.65±0.1 [0.065±0.004] 0.80±0.025 [0.031±0.001] 0.90±0.10 [0.035±0.004] 2X 10°±2'</p> <p>MATING TAB NOTES: 4. MAT'L: BRASS. FINISH: SUGGESTED NO PLATING.</p> <p>(92.4 +/- 5.0) 50.8 +/- 5.0</p>									WITHOUT STABILIZER	WITH STABILIZER	DIM. "A"	2.20 [0.087] MIN.	4.20±0.15 [0.165±0.006]	DIM. "B"	7.40 [0.291] MIN.	7.98 [0.314] MIN.	DIM. "C"	5.90 [0.232] MAX.	(7.6)														
	WITHOUT STABILIZER	WITH STABILIZER																															
DIM. "A"	2.20 [0.087] MIN.	4.20±0.15 [0.165±0.006]																															
DIM. "B"	7.40 [0.291] MIN.	7.98 [0.314] MIN.																															
DIM. "C"	5.90 [0.232] MAX.	(7.6)																															
REV.	DESCRIPTION	DATE	BY	SCALE: 1:1 DIMENSIONS: All dimensions are in MM with a tolerance of +/- 3.0 unless otherwise specified. DRAWN BY: STEVEN PILKINGTON CHECKED BY: JUSTIN BAKER		CUSTOMER NAME: _____ CUSTOMER PART NO.: _____ DESCRIPTION: 2" LIF, POS LOCK, .250, DOUBLE-END LEADS, BRASS, F-F ASSEMBLY PART NO.: ASRSFSRSF16K51A DRAWING NO. & REVISION: GAM-127 REVISED: 3/15/2016																											

