



Click [here](#) for the 3D model.

### Dimensions

D	10mm +/-0.5mm
L	20mm +/-1mm
L1	26mm MIN
LL	31mm +3/-2mm
F	0.8mm +/-0.03mm

### Packaging Specifications

Packaging	T&R, Plastic Tape
Packaging Quantity	500

### General Information

Series	PEG124_125C
Dielectric	Aluminum Electrolytic
Style	Axial
Description	Long Life Axial Aluminum Electrolytic
Features	Long Life
RoHS	Yes
Lead	Wire Leads
AEC-Q200	No
Halogen Free	Yes
Component Weight	3 g
Miscellaneous	Life Calculation Based On Maximum Ripple Current, Please Contact KEMET For More Information.
Notes	L1 is KEMET's recommendation for minimum distance between symmetrical Lead bend. Available only for Customer specific part numbers. Lead bend dimensions must be specified and confirmed per article.

### Specifications

Capacitance	68 uF
Capacitance Tolerance	-10/+30%
Voltage DC	16 VDC
Temperature Range	-40/+125°C
Rated Temperature	125°C
Life	2000 Hrs
Resistance	2400 mOhms (100Hz 20C), 1600 mOhms (100kHz 20C)
Ripple Current	0.13 Amps (100Hz 125C), 0.95 Amps (5kHz 60C), 0.36 Amps (5kHz 125C)
Leakage Current	3 uA (5min 20°C)
Inductance	5 nH (ESL)