
## Contact Detail: 520-P.C. Tail .025x.024(0.64x0.61) - Tail LG.=.215(5.46)



## Features

- UL Recognized
- .150 (3.81) Contact Spacing x .130 (3.30) or .150 (3.81) Row Spacing with Staggered Grid
- Plug and Receptacle in 14 or 36 Contact Sizes .
- Edacon Hermaphroditic Contact Mating Design .
- Contact Termination Options Include: Crimp, P.C. Tail, Wire Hole and Wire Wrap
- Mating and Unmating Simplified with use of Actuating Screws
- Optional Covers with Side or Top Entry Cable Clamp in Plastic or Metal Material Available for All Connector Sizes
- Versatile Metal Cover Design Permits Assembly and Disassembly after Cabling is Complete plus Cable Entry Style Flexibility
- Actuating Screws, Locknuts, Polarizing Hardware, Covers and Contacts Suitable for either Plug or Receptacle
- Polarizing Hardware Adjustable for 288 Mating Combinations
- Tools Available for Contact Installation, Removal and Crimping and Polarizing Changes

## See Accompanying Pages for:


- PC Tail Lavout
- Cutout Panel Details
- Cover Details

## **Specifications**

- Insulator Material:Polycarbonate, Colour: Grev
- Contact Material: Phosphor Bronze Alloy CA-510 .
- Contact Plating: Gold over Nickel for Entire Contact •
- Cover Material: Polycarbonate, Colour: Green, or Die-. Cast Zinc, Finished with Grey Enamel Paint
- Current Rating: 8.5 Amperes •
- Contact Resistance: 10 Milliohms Maximum •
- Dielectric Withstanding Voltage: 2000 V AC rms at • Sea Level
- Insulation Resistance: 5000 Megohms Minimum •
- Operating Temperature: -65 to +125 Degrees C •
- . Insertion and Withdrawal Force: 2 to 16 oz (0.56 to 4.45 N) per Contact Position

519 Assembly	ACAD REFERENCE NO. 519 Assembly
	DRAWN: J.LEE DATE: JUNE 18, 2009
Part Number: 519-036-520-301	CHECKED: DATE:
	AND SPECIFICATIONS SCALE: 1:1 SHEET 1 OF 4
IORONIO, ONIARIO SHALL NOT BE RI	TY OF EDAC INC.,AND EPRODUCED,OR COPIED DRAWING NUMBER ISSUE
	SALE OF APPARATUS 510 Accomply 1









519 Assembly	ACAD REFERENCE NO. 519 Assembly			
Cut-Out Panel Detail		DRAWN: J.LEE	DATE: JUN	VE 18, 2009
		CHECKED:	DATE:	
	THESE DRAWINGS AND SPECIFICATIONS	SCALE:	SHEET :	3 OF 4
I CIII IN INTERIO	ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE	DRAWING NUMBER		ISSUE
YOUR CONNECTION TO QUALITY & SERVICE	MANUFACTURE OR SALE OF APPARATUS	519 Assembly		1

Top	9"	"C"	Side E	ntry		F"	STER CLARGE CLA	ORIGINAL	
Cover for Cover Connector Materia	Clamp Size	"A"	"В"	"C"	"D"	"E"	"F"	"G"	
14 Pin Plastic	Standard	1.605 (40.77)	1.325 (33.66)	0.906 (23.01)	1.190 (30.23)	0.715 (18.16)	0.450 (11.43)	0.450 (11	.43)
14 Pin Metal	Standard	1.539 (39.09)	1.325 (33.66)	0.906 (23.01)	1.120 (28.45)	0.686 (17.42)	0.446 (11.33)	0.490 (12	
36 Pin Plastic	Standard	2.460 (62.48)	2.010 (51.05)	1.530 (38.86)	1.985 (50.42)	0.910 (23.11)	0.650 (16.51)	0.500 (12	.70)
36 Pin Plastic	Large	2.460 (62.48)	2.010 (51.05)	1.530 (38.86)	1.985 (50.42)	1.110 (28.19)	0.650 (16.51)	0.608 (15	.44)
36 Pin Metal	Standard	2.206 (56.03)	2.006 (50.95)	1.566 (39.78)	1.766 (44.86)	0.875 (22.23)	0.720 (18.29)	0.575 (14	.61)
			519 Asser	nbly Panel Detail			ACAD REFERENCE DRAWN: J.LEE	NO. 519 Assembl	-