<u> </u>	G	п	m	τ	5	0		Þ		
	VV Thread	ØS								
						LAYOUT	SHOWN AS EXAMPLE			
		Keying Shown a	as example							
CHARACTERISTICS		Г	Connector dimension	7						
Standard : Based on MIL-DTL-38999	ieries III	F	DimNominalØS25 Max	-						
-Shell Material : Composite -Shell Plating : Nickel		E	Z' 31.5 Max				e liable for any non-conformit e Products which does not co			
-Insulator : Thermoplas	tic	L	VV THREAD M15x1-6g	L		the Specifications issue	ed by either of the Parties or I	by a third party		
-Contacts : Copper Allo						(professional	recommendation, technical n	otice.)		
-Seals & Grommet : Silicon Elast							Country Jurisc	liction & Control List	J	
-Contact Plating : Gold over c	opper Alloy 0.8µm minimum						FR	Not Listed		
-Durability : 500 Mating	cycles									
-Delivered with Souriau contacts and	Accessories					PN:	8D511M01AN			
-Temperature Range : -65°C to +2	00°C			ſ	A 16-10	-2016 First Release			_	_
-Salt Spray : 2000 hours										
Mass : 12.8 g ± 105				-	ISS DA Designed By:	TE Latest modification - b Date:	<u>/</u>	CUSTOMER DRAWING	MOD N°	
				-	TITLE		Composite Plug 8	D series		_
	8D 5 - 11 M			-	SCALE		eneral linear	NPRDS / PROJECT		
BASIC SERIES:	8D 5 - 11 M	01 A N					Tolerances:	859		
SHELL TYPE : Plug with RFI Shielding					NA		±	This document is the pro	perty of	
CONTACT TYPE : Standard Crimp Co	ntact			NTATION : N	SOURI	AU WWW.SO	URIAU.COM	SOURIAU it must not be reprodu	ced or	
SHELL SIZE : 11			CONTACT TYPE : PIN(5		EODMAAT			communicated without pe		
PLATING : M = Nickel			CONTACT LAY	OUT : 11-01	FORMAT A3		DURIAU DRG N°		SHEET	
							D511M01AN-C			

F	Ŧ	G	<del>ات</del>	m	D	0
		Contact Layout				
4	/	01				
_	(	1#12				
	Ctc A	11-01 X Y 0 0				
ω						
	_				[	SOURIAU shall not be liable for any
						due to a use of the Products wh the Specifications issued by either of (professional recommendat
S						PN: 8D511N
					A 16-10-20 ISS DATE	016 First Release
					Designed By:	Date:
<b>→</b>					SCALE NA	General linear Tolerances: ±
					SOURIA	
					FORMAT A3	SOURIAU 8D511M
	Н	G	F	E	D	C

