

### product type designation

product description




### PROFIBUS FC Standard Cable GP

Standard bus cable (2 wires), preferred length, not assembled

PROFIBUS FC Standard, bus cable 2-wire, shielded, special configuration for Quick assembly 20 m.

|  |  |
|--|--|
| suitability for use  | Standard cable specially designed for fast, permanent installation                     |
| cable designation  | 02YSY (ST) CY 1x2x0,64/2,55-150 VI KF 40 FR  |
| wire length  | 20 m   |
| <b>electrical data</b>   |  |
| attenuation factor per length  |  |
| <ul style="list-style-type: none"> <li>at 9.6 kHz / maximum</li> <li>at 38.4 kHz / maximum</li> <li>at 4 MHz / maximum</li> <li>at 16 MHz / maximum</li> </ul>   | 0.0025 dB/m<br>0.004 dB/m<br>0.022 dB/m<br>0.042 dB/m                                  |
| impedance  |  |
| <ul style="list-style-type: none"> <li>rated value</li> <li>at 9.6 kHz</li> <li>at 38.4 kHz</li> <li>at 3 MHz ... 20 MHz</li> </ul>  | 150 Ω<br>270 Ω<br>185 Ω<br>150 Ω   |
| relative symmetrical tolerance   |  |
| <ul style="list-style-type: none"> <li>of the characteristic impedance at 9.6 kHz</li> <li>of the characteristic impedance at 38.4 kHz</li> <li>of the characteristic impedance at 3 MHz ... 20 MHz</li> </ul> | 10 %<br>10 %<br>10 %   |
| loop resistance per length / maximum   | 110 mΩ/m   |
| shield resistance per length / maximum   | 9.5 Ω/km   |
| capacity per length / at 1 kHz   | 28.5 pF/m  |
| operating voltage  |  |
| <ul style="list-style-type: none"> <li>RMS value</li> </ul>  | 100 V  |
| <b>mechanical data</b>   |  |
| number of electrical cores   | 2  |
| design of the shield   | Overlapped aluminum-clad foil, sheathed in a braided screen of tin-plated copper wires |
| type of electrical connection / FastConnect  | Yes  |
| outer diameter   |  |
| <ul style="list-style-type: none"> <li>of inner conductor</li> <li>of the wire insulation</li> <li>of the inner sheath of the cable</li> <li>of cable sheath</li> </ul>  | 0.65 mm<br>2.55 mm<br>5.4 mm<br>8 mm   |
| symmetrical tolerance of the outer diameter / of cable sheath  | 0.4 mm   |
| material   |  |
| <ul style="list-style-type: none"> <li>of the wire insulation</li> <li>of the inner sheath of the cable</li> </ul>   | polyethylene (PE)<br>PVC   |

|   |  |
|---|--|
| <ul style="list-style-type: none"> <li>• of cable sheath</li> </ul>   | PVC  |
| color   |  |
| <ul style="list-style-type: none"> <li>• of the insulation of data wires</li> <li>• of cable sheath</li> </ul>  | red/green<br>Violet  |
| bending radius  |  |
| <ul style="list-style-type: none"> <li>• with single bend / minimum permissible</li> <li>• with multiple bends / minimum permissible</li> </ul>   | 37.5 mm<br>75 mm   |
| tensile load / maximum  | 100 N  |
| weight per length   | 78 kg/km   |
| <b>ambient conditions</b>   |  |
| ambient temperature   |  |
| <ul style="list-style-type: none"> <li>• during operation</li> <li>• during storage</li> <li>• during transport</li> <li>• during installation</li> <li>• note</li> </ul>   | -40 ... +75 °C<br>-40 ... +75 °C<br>-40 ... +75 °C<br>-40 ... +75 °C<br>Electrical properties measured at 20 °C, tests according to DIN 47250 part 4 respectively DIN VDE 0472   |
| fire behavior   | flame resistant according to IEC 60332-3-24 (Category C) and UL 1685 (CSA FT 4)  |
| class of burning behaviour / according to EN 13501-6  | Eca  |
| chemical resistance   |  |
| <ul style="list-style-type: none"> <li>• to mineral oil</li> <li>• to grease</li> <li>• to water</li> </ul>   | oil resistant according to IEC 60811-2-1 (4 h / 70°C)<br>Conditional resistance<br>conditional resistance  |
| radiological resistance / to UV radiation   | resistant  |
| <b>product features, product functions, product components / general</b>  |  |
| product feature   |  |
| <ul style="list-style-type: none"> <li>• halogen-free</li> <li>• silicon-free</li> </ul>  | No<br>Yes  |
| <b>standards, specifications, approvals</b>   |  |
| UL/ETL listing / 300 V Rating   | Yes; c(ETL)us, CMG / (ETL)us CL3 / Sun Res   |
| UL/ETL style / 600 V Rating   | Yes; cRUus AWM 21694 AWM I A/B 60°C 600V FT2   |
| certificate of suitability  |  |
| <ul style="list-style-type: none"> <li>• EAC approval</li> <li>• CE marking</li> <li>• UL approval</li> <li>• RoHS conformity</li> </ul>  | Yes<br>Yes<br>Yes<br>Yes   |
| Marine classification association   |  |
| <ul style="list-style-type: none"> <li>• American Bureau of Shipping Europe Ltd. (ABS)</li> <li>• French marine classification society (BV)</li> <li>• Det Norske Veritas (DNV)</li> <li>• Germanische Lloyd (GL)</li> <li>• Lloyds Register of Shipping (LRS)</li> <li>• Nippon Kaiji Kyokai (NK)</li> <li>• Polski Rejestr Statkow (PRS)</li> </ul>   | No<br>No<br>No<br>No<br>No<br>No<br>No   |
| reference code  |  |
| <ul style="list-style-type: none"> <li>• according to IEC 81346-2</li> <li>• according to IEC 81346-2:2019</li> </ul>   | WG<br>WGB  |
| <b>further information / internet-Links</b>   |  |
| Internet-Link   |  |
| <ul style="list-style-type: none"> <li>• to web page: selection aid TIA Selection Tool</li> <li>• to website: Industrial communication</li> <li>• to website: Industry Mall</li> <li>• to website: Information and Download Center</li> <li>• to website: Selection guide for cables and connectors</li> <li>• to website: Image database</li> <li>• to website: CAx-Download-Manager</li> <li>• to website: Industry Online Support</li> </ul> | <a href="http://www.siemens.com/tia-selection-tool">http://www.siemens.com/tia-selection-tool</a><br><a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a><br><a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a><br><a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a><br><a href="https://sie.ag/2QdlxcP">https://sie.ag/2QdlxcP</a><br><br><a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a><br><a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a><br><a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a> |
| <b>last modified:</b>   | 10/30/2021    |

