



注記
NOTES

- 適用ハウジング : 52133-****
APPLICABLE HOUSING : 52133-****
- メッキ仕様
PLATING

接点部 : 金メッキ 1.27 μm MIN.
CONTACT AREA : Au 1.27 μm MIN.
圧着部 : 半田メッキ 1.0 μm MIN.
CRIMPING AREA : Sn-Pb 1.0 μm MIN.
下地メッキ : ニッケルメッキ 1.0 μm MIN.
UNDER PLATING : Ni 1.0 μm MIN.

- 適用電線範囲 : UL 1015 AWG#14~18
APPLICABLE WIRE RANGE : UL 1015 AWG #14~18

連鎖状 CHAIN	50095-9064
端子形状 FORM	MATERIAL NO.
MODEL NO.	50095-****

材料 MATERIAL	黄銅 BRASS	REVISED EC NO: J2009-1270 DRWN: KAKURAA 2008/12/16 CHKD: T. HARUYAMA 2008/12/16 APPR: NUKITA 2009/01/14	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY	SCALE 5:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	
仕上げ FINISH	注記参照 SEE NOTES		10 UNDER	±0.2	DRAWN BY Y. ITO	DATE '87/6/19	TITLE MULTI MOUNT MALE CRIMP TERM.		
適用電線範囲 WIRE RANGE	注記参照 SEE NOTES		10 OVER 30 UNDER	±0.25	CHECKED BY Y. ITO	DATE	APPROVED BY A. ASO		
被覆外径 INS. RANGE	∅2.9-∅3.8		30 OVER	±0.3	APPROVED BY A. ASO	DATE	MATERIAL NO. SEE TABLE		
		ANGULAR	±3 °	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		DOCUMENT NO. SD-50095-002		SHEET NO. 1 OF 1	
				THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION					