



Click [here](#) for the 3D model.

### Dimensions

|           |                 |
|-----------|-----------------|
| Chip Size | 0805            |
| L         | 2mm +/-0.3mm    |
| W         | 1.25mm +/-0.3mm |
| T         | 1mm +/-0.20mm   |
| S         | 0.75mm MIN      |
| B         | 0.5mm +/-0.25mm |

### Packaging Specifications

|                    |                          |
|--------------------|--------------------------|
| Packaging          | T&R, 180mm, Plastic Tape |
| Packaging Quantity | 2500                     |

### General Information

|                  |   |
|------------------|---|
| Series           | ESD SMD Auto X7R  |
| Style            | SMD Chip  |
| Description      | SMD, MLCC, Temperature Stable, Electro Static Discharge, Automotive Grade |
| Features         | Temperature Stable, Automotive Grade                                      |
| RoHS             | Yes   |
| Termination      | Flexible Termination  |
| Marking          | No  |
| Qualifications   | AEC-Q200  |
| AEC-Q200         | Yes   |
| Component Weight | 13 mg   |
| Shelf Life       | 78 Weeks  |
| MSL              | 1   |

### Specifications

|  |  |
|--|--|
| Capacitance  | 0.033 uF   |
| Measurement Condition  | 1 kHz 1.0Vrms                                      |
| Capacitance Tolerance  | 10%  |
| Voltage DC   | 100 VDC  |
| ESD Level per AEC-Q200   | 25,000 V ESD Level                                 |
| Dielectric Withstanding Voltage                                    | 250 VDC  |
| Temperature Range  | -55/+125°C   |
| Temperature Coefficient  | X7R  |
| Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC) | 15%, 1kHz 1.0Vrms                                  |
| Dissipation Factor   | 2.5% 1 kHz 1.0Vrms                                 |
| Aging Rate   | 3% Loss/Decade Hour:<br>Referee Time is 1000 Hours |
| Insulation Resistance  | 30.303 GOhms                                       |