


Specification Sheet

Part Number: 157-00343



Low-profile head allows mounts to stack, providing more mounting versatility from a single stud.

Four-pawl, three-tooth design delivers outstanding stud retention to keep bundles secure.

PA46 material option allows use in high-heat applications.

Low Profile M10 Stud Mount Tie, 7.5" Tie, 80lb Tensile Strength, PA46, Brown, 3500/pkg

Article Number 157-00343

Type T80ROSLPSB10U

Color Brown (BN)

Quantity Per carton

Product Description One-piece mounting ties offer a complete solution by both bundling cable and at the same time providing a mounting solution. HellermannTyton's one-piece mounting ties offer the ideal combination of high specification materials and superior design to suit the mounting and bundling needs of complex applications.

Short Description Low Profile M10 Stud Mount Tie, 7.5" Tie, 80lb Tensile Strength, PA46, Brown, 3500/pkg

Global Part Name T80ROSLPSB10U-PA46-BN

Minimum Tensile Strength (Imperial)	80.0
Minimum Tensile Strength (Metric)	355
Length L (Imperial)	8.5
Length L (Metric)	215.9
Fixation Method	Stud Mount
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Width W (Imperial)	0.22
Width W (Metric)	10.0
Bundle Diameter Min (Imperial)	0.14
Bundle Diameter Min (Metric)	3.5
Bundle Diameter Max (Imperial)	1.97
Bundle Diameter Max (Metric)	50.0
Cable Ties	157-00343
Height H (Imperial)	0.28

Height H (Metric)	7.0
Mounting Hole Diameter D (Imperial)	0.39" x 0.06
Mounting Hole Diameter D (Metric)	M10 x 1.50
Stud Diameter (Metric)	10.0 mm
Stud Diameter (Imperial)	0.39
Material	Polyamide 4.6 (PA46)
Material Shortcut	PA46
Flammability	UL 94 V-2
Halogen Free	Yes
UV Resistant (Yes/No)	No
Operating Temperature	-40°F to +266°F (-40°C to +130°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	3500
Package Quantity (Metric)	3500

Customs Number

3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)