




.XX ±0.13 .XXX ±0.05

	ORI
L-L-L	







NOTES:


MATERIAL: HOUSING: SHELL: CONTACT:

OPERATING TEMPERATURE:

WITHSTANDING VOLTAGE:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, GOLD FLASH PLATED


30A (CURRENT) **POWER/CO-AX CONTACT RATING:** (IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE: $10m\Omega$ MAX. INSULATOR RESISTANCE: 5000MΩ min. DIELECTRIC



	COMBINATION D-SUB		SW REFERENCE NO.: 629 COMBO ASSEMBLY							
COMBI			DRAWN: C.B			DATE: JAN. 01/2019			19	
			CHECKED:			DATE:				
EDAC	EDAC INC TORONTO, ONTARIO CANADA YOUR CONNECTION TO QUALITY & SERVICE	ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS	SCALE:	(IN C.A.D. 1:	1)	SHEET	1	OF	2	
			DRAWING NUMBER: 629-13W3			/3240-3N2			ISSUE	
YOUR CONNECTION TO QUALITY &			PART NUI	MBER:	629-13W3	3240-3N2			1	

1000V AC rms

-55°C ~ 125°C





THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.



