



CORE DIMENSIONS		28T0201-100			
UNCOATED CORE					
	MM	INCHES		MM	INCHES
OD	5.10	(.201)	±	.15	(.006)
ID	1.45	(.057)	±	.15	(.006)
TH	3.40	(.134)	±	.15	(.006)

WEIGHT / K 0.3113 KGS .6862 LBS  
 INITIAL PERMEABILITY 850

ROOM TEMPERATURE ELECTRICAL SPECIFICATION								
	MIN. TOL.	MIN. ( $\mu H$ )	NOM. ( $\mu H$ )	MAX. ( $\mu H$ )	MAX. TOL.	FREQ. (kHz)	VOLT. (mV)	TURNS
L1-1T(REF.)	-25.0%	0.55	0.727	0.91	25.0%	100	2.42	1
NET IMPEDANCE	MIN ( $\Omega$ )	MIN TOL.	NOM ( $\Omega$ )	MAX	MAX TOL.	FREQ. (MHz)		TURNS
Z1 (REF.)	-	-	36	-	-	25		1
Z2	41	(-25%)	55	-	-	100		1

NOTES:

1. Cosmetic Specification refer to WI-QA-015.



Rev	Description	Date	INT
A	New release	2020/4/19	WS

Date: 2020/4/19	Tooling: T0201	Rev: A
Drawn By: WS	Title # 28T0201-100	

Steward This document contains information which is proprietary to Steward. No production or publication of this document in whole or in part shall be made without written authorization from Steward.