

Master cable - RCK-TWUM/BL12/ 5,0PUR-U - 1684030

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



M23 socket, angled, 12-pos., with 5 m master cable, pin 9 and 10 bridged



Key Commercial Data

| | |
|--------------|---------------|
| Packing unit | 1 pc |
| GTIN | |
| GTIN | 4017918172084 |
| Sales Key | 02 |

Technical data

General

| | |
|-----------------------------------|----------------------------------------------------------------------------------------------------|
| Rated voltage | 48 V AC 60 V DC |
| Number of positions | 12 |
| Sensor/actuator connection system | M12 socket |
| Note | The master cable is earmarked for use on the sensor/actuator boxes with an M23 plug-in connection. |

Ambient conditions

| | |
|---------------------------------|-----------------------------------|
| Degree of protection | IP65 IP67 |
| Ambient temperature (operation) | -40 °C ... 125 °C (Plug / socket) |

Master cable data/connection data

| | |
|-------------------|---------------------|
| Connection method | M23 plug connection |
| Length of cable | 5 m |

Insulation material

| | |
|----------------------------------------|----------|
| Housing material | PUR |
| Material of contact, master cable side | CU alloy |

Master cable - RCK-TWUM/BL12/ 5,0PUR-U - 1684030

Technical data

Insulation material

| | |
|----------------------------------------------------------|-------------|
| Material of contact surface, master cable side | Gold-plated |
| Material of the contact carrier on the master cable side | PA |

Connection assignment

| | |
|---------------------------------------|----------------------------|
| Slot/position = pin = conductor color | 1 / 4 (A) = 1 = WH |
| | 2 / 4 (A) = 2 = GN |
| | 3 / 4 (A) = 3 = YE |
| | 4 / 4 (A) = 4 = GY |
| | 5 / 4 (A) = 5 = PK |
| | 6 / 4 (A) = 6 = RD |
| | 7 / 4 (A) = 7 = BK |
| | 8 / 4 (A) = 8 = VT |
| | 1-8 / 1 (+ 48 V) = 11 = BN |
| | 1-8 / 3 (0 V) = 9+10 = BU |
| | 1-8 / 5 (PE) = 12 = GN/YE |

Cable

| | |
|-------------------------------------------------|---------------------------------------------------------------------------------|
| Cable type | PUR/PVC black |
| Cable type (abbreviation) | PUR |
| Cable abbreviation | LiYY11Y-HF |
| UL AWM style | 20549 (80°C/300 V) |
| Conductor cross section | 8x 0.34 mm ² (Signal line) |
| | 3x 0.75 mm ² (power line) |
| AWG signal line | 22 |
| AWG power supply | 18 |
| Conductor structure signal line | 19x 0.15 mm |
| Conductor structure, voltage supply | 42x 0.15 mm |
| Core diameter including insulation | 1.3 mm ±0.1 mm (Signal line) |
| | 1.8 mm ±0.1 mm (power line) |
| Wire colors | brown, blue, green/yellow, white, green, yellow, gray, pink, red, black, violet |
| Overall twist | Wires twisted in layers |
| External sheath, color | black RAL 9005 |
| Inner sheath thickness | ≥ 0.15 mm |
| Outer sheath thickness | ≥ 0.38 mm |
| External cable diameter D | 8.5 mm ±0.2 mm |
| Minimum bending radius, fixed installation | 7.5 x D |
| Minimum bending radius, flexible installation | 10 x D |
| Number of bending cycles | 1500000 |
| Minimum bending radius, drag chain applications | 10 x D |
| Traversing path | 2 m |
| Traversing rate | 2 m/s |

Master cable - RCK-TWUM/BL12/ 5,0PUR-U - 1684030

Technical data

Cable

| | |
|---------------------------------|------------------------------------------------------------------------------------------------|
| Cable weight | 107.4 kg/km |
| Outer sheath, material | PUR |
| Material, inner sheath | PVC |
| Material conductor insulation | PVC |
| Conductor material | Bare Cu litz wires |
| Insulation resistance | ≥ 5 MΩ*km |
| Conductor resistance | ≤ 53 Ω/km (Signal line) ≤ 26 Ω/km (power line) |
| Nominal voltage, cable | 300 V AC |
| Test voltage Core/Core | 2000 V (50 Hz, 5 min.) |
| Special properties | Silicone-free |
| Flame resistance | DIN EN 50265 |
| Resistance to oil | according to VDE 0472 Part 803 |
| Other resistance | Highly resistant to acids, alkaline solutions and solvents |
| Ambient temperature (operation) | -40 °C ... 90 °C (cable, fixed installation) -5 °C ... 80 °C (cable, flexible installation) |

Environmental Product Compliance

| | |
|------------|-----------------------------------------------------------------------------------------------------|
| | Lead 7439-92-1 |
| China RoHS | Environmentally Friendly Use Period = 50 |
| | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

| | | |
|-----|-------------------------------------------------------------------------------------|---------|
| EAC |  | B.00767 |
|-----|-------------------------------------------------------------------------------------|---------|

Phoenix Contact 2019 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>