## **Material Safety Data Sheet**



**Revision Number: 001.2** Issue date: 09/14/2010

# 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: **NC-OO Desoldering Wick** IDH number: Product type: Desoldering wick Item number: M291017 Region: United States

Company address: **Contact information:** Henkel Corporation Telephone: 860.571.5100

One Henkel Way MEDICAL EMERGENCY Phone: Poison Control Center Rocky Hill, Connecticut 06067

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

#### **HAZARDS IDENTIFICATION**

**EMERGENCY OVERVIEW** 

Physical state: Solid **HEALTH:** FLAMMABILITY: Color: Copper 0 PHYSICAL HAZARD: Odor: None 0

See MSDS Section 8 Personal Protection: **CAUTION:** 

MAY CAUSE EYE. SKIN AND RESPIRATORY TRACT IRRITATION.

MAY CAUSE ALLERGIC SKIN REACTION.

Relevant routes of exposure: Skin, Inhalation, Eyes

**Potential Health Effects** 

Inhalation: Fumes evolved at soldering temperatures will irritate the nose, throat and lungs.

Prolonged or repeated skin contact may cause irritation, skin sensitization and argyria (a non-Skin contact:

toxic, cosmetic blue-gray discoloration of the skin and mucous membranes that is irreversible).

Eye contact: Causes eye irritation.

Ingestion: Not expected under normal conditions of use. Wire strands could cause internal injury

Existing conditions aggravated by

exposure:

Eye, skin, and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR

1910.1200).

See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Copper	7440-50-8	60 - 100

### 4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. If symptoms develop and persist, get medical attention.

Skin contact: Wash with soap and water. If symptoms develop and persist, get medical

attention.

IDH number: 291017 Product name: NC-OO Desoldering Wick Eye contact: Flush eye(s) immediately with plenty of water. If eye irritation persists, consult

a specialist.

Ingestion: Wire strands could cause internal injury Induce vomiting immediately and call

a physician.

#### 5. FIRE FIGHTING MEASURES

Flash point:

Autoignition temperature:

Not available

Flammable/Explosive limits - lower:

Not available

Flammable/Explosive limits - upper:

Not available

Extinguishing media: Will not burn. Do not use water on molten metal.

**Special firefighting procedures:** Firefighters should wear self-contained breathing apparatus. Water may be

ineffective, but may be used to cool exposed containers to prevent pressure build-up and possible auto-ignition or explosion when exposed to extreme

heat. If water is used, fog nozzles are preferable.

Unusual fire or explosion hazards: None

Hazardous combustion products: High temperatures may produce heavy metal dust, fumes or vapors. The flux

medium will give rise to irritating fumes.

### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow product to enter sewer or waterways.

Clean-up methods: Scrape up as much material as possible.

### 7. HANDLING AND STORAGE

**Handling:** Wash thoroughly after handling.

**Storage:** No special procedures.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Copper	1 mg/m3 TWA (as Cu) Dust and mist. 0.2 mg/m3 TWA Fume.	1 mg/m3 TWA (as Cu) Dust and mist. 0.1 mg/m3 TWA (as Cu) Fume.	None	None

**Engineering controls:** Ensure adequate ventilation.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

**Eye/face protection:** Safety goggles or safety glasses with side shields.

Skin protection: Gloves should be used if resin causes skin irritation.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Solid Color: Copper Odor: None Odor threshold: Not available pH: Not available

Vapor pressure: Negligible vapor pressure at ambient temperatures.

Boiling point/range: Not available

Melting point/ range: 1,083 °C (1,981.4 °F) (copper)

8.9

Specific gravity: Vapor density: Not available Flash point: Not applicable Flammable/Explosive limits - lower: Not available Flammable/Explosive limits - upper: Not available Autoignition temperature: Not available **Evaporation rate:** Not available Solubility in water: Insoluble Partition coefficient (n-octanol/water): Not available VOC content: Zero

#### 10. STABILITY AND REACTIVITY

Stability: Stable under recommended storage conditions.

Hazardous reactions: Will not occur.

Hazardous decomposition products: Oxides of Metals in Section 2. Oxides of carbon. Irritating fumes.

Incompatible materials: Acids and bases. Strong oxidizing agents.

Conditions to avoid: Reacts with concentrated nitric acid to produce toxic fumes of nitrogen oxides.

### 11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen	
nazardous components	NTF Carcinogen	IARC Carcinogen	(Specifically Regulated)	
Copper	No	No	No	

Hazardous components	Health Effects/Target Organs
Copper	Allergen, Blood, Central nervous system, Developmental, Gastrointestinal, Immune system, Irritant, Kidney, Liver, Mutagen, Sensory, Skin

### 12. ECOLOGICAL INFORMATION

**Ecological information:** 

No specific studies have been conducted by Henkel on the ecotoxicity or environmental fate of this material; however, commonly available data on the material indicate that uncontrolled releases to soil, ground water, or surface waters could entail acute and/or chronic ecological effects, depending on the quantity and concentration of such releases. Releases of volatile components to the atmosphere are not believed to entail significant ecological consequences provided such releases are within the exposure levels set forth in this document. Accordingly, all appropriate measures should be taken to avoid uncontrolled releases to the environment, and any spills or other uncontrolled releases which may occur should be contained and cleaned up immediately in accordance with Section 6.

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not available

#### 14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:
Not regulated
None
None
None

International Air Transportation (ICAO/IATA)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:
Not regulated
None
None
None

Water Transportation (IMO/IMDG)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:
Not regulated
None
None

#### 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12(b) Export Notification: None above reporting de minimus

CERCLA/SARA Section 302 EHS: None above reporting de minimus CERCLA/SARA Section 311/312: Immediate Health, Delayed Health

CERCLA/SARA Section 311/312: Immediate Health, Delayed Health CERCLA/SARA 313: This product contains the following

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). Copper (CAS# 7440-50-8).

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

**Canada Regulatory Information** 

WHMIS hazard class:

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List. D.2.A, D.2.B

#### 16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format

Prepared by: Lou Fabrizio, Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

IDH number: 291017 Product name: NC-OO Desoldering Wick