

Ratings

Voltage: 300 V
Temperature: -25 ~ 80 °C
Flammability: VW-1

Conductor

Conductor count: 3
Gauge: 26 AWG 0.14 mm²
Material: tinned copper strands
Strand size: Ø 0.16 x 7
Resistance at 20 °C: 150 Ω /km max

Insulator

Material: PVC
Color: black, white, red
Diameter: Ø 1.1 ±0.1 mm
Nominal thickness: 0.29 mm
Resistance at 20 °C: 10 MΩ /km min



Outer jacket

Material: PVC
Color: white
Diameter: Ø 4.0 ±0.2 mm
Nominal thickness: 0.80 mm

Wire marking: E339579 UL AWM STYLE 2464 26 AWG 80°C
300V VW-1 --- cUL AWM I/II A 80°C 300V FT1 LF TENSILITY

Tests

Insulation tensile strength: 2.11 kgf/mm²
Jacket tensile strength: 1.05 kgf/mm²
After aging at 113 ±2 °C for 7 days:
Minimum tensile strength 70 % original
Minimum elongation 65 % original
Heat shock: 121 ±1 °C /1 hour, no observed degradation
Deformation: 121 ±1 °C /1 hour, ≤ 50 %
Cold bend: -10 ±2 °C /1 hour, no observed cracking



Revision:	Date:	Description:
A	06/25/2014	Initial release
A1	09/06/2018	Increased operating temperature range

Prepared:

Verified:

Dimensions are in millimeters.
Tolerances:
X: ± 0.5 mm
X.X: ± 0.3 mm
X.XX: ± 0.05 mm

Notes:
RoHS and REACH compliant

Function test: no open, no short circuit, no intermittent

Description:
Wire, 3C TS, 26 AWG, UL2464, 300V, 80C, 4.0 mm, VW-1, PVC, white

TENSILITY

tel 1.541.323.3228 800 877.670.7118
fax 1.541.323.4202 web tensility.com

Size: A	Part number: 30-00378
Scale: 10:1	Sheet 1 of 1