Data Sheet




Coaxial PCB Connector 82_MCX-S75-0-2/111_N

Description

Straight PCB jack

Interface Standards IEC 60169-36_CECC 22220



Technical Data

Electrical Data

 $\begin{array}{ll} \text{Impedance} & 75 \, \Omega \\ \text{Interface frequency max.} & 6 \, \text{GHz} \end{array}$

Mechanical Data

Board mounting type edge mount Weight 0.0009 kg

Environmental Data

Operating temperature -65 °C to 165 °C 2011/65/EU (RoHS - including 2015/863 and 2017/2102) compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Brass	SUCOPRO Plating
Body	Brass	SUCOPRO Plating
Insulator	PFA / PTFE	

Related Documents

Outline drawing DOU-00013375
Catalogue drawing DCA-00013377

Ordering Information

 Single package
 82_MCX-S75-0-2/111_NE

 Bulk 100 pcs package
 82_MCX-S75-0-2/111_NH

Remarks

PCB connector without stand-offs

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.