



AEROS
Unsurspass
Technic

A INC
Strain Reli

Aerosusa.com
service@aerosusa.com
855.393.9905

RQG-M



Plastic connector, quick-type, straight, metric outer thread, integrated snap-in sleeve with sealing, high density. Certain sizes are UL 514B listed, see the below product details for which sizes. For installation in accordance with Article 356 of ANSI / NFPA 70, National Electric Code, NEC.

Material: PA plastics

Temperature:

-40°C ... +120°C

-40°F ... +248°F

Protection Class: IP 68 | IP 69K

Properties:

- Rational tubing assembly due to one-piece screw connector with push-in lock for coarse and fine profile conduits
- Simple dismounting by displacing the snap-in sleeve
- Smallest out dimensions to be used under confined conditions
- Free of silicone, cadmium and halogen
- Self-extinguishing
- Fit for high mechanical stress
- Impact-resistant

Note:

Lock-nuts and sealing washers sold separately. See below for corresponding accessories.

CERTIFICATIONS



"Unsurpassed in Cable Protection and Strain Relief"

2409 Herr St.
Harrisburg, PA 17103



Aerosusa.com
service@aerosusa.com
855.393.9905

Technical Data Sheet

Product #	Color	Trade Size	AD	Thread	I (in)	B (in)	C (in)	D (in)	WS (in)	Ib/100	UL Listed	Pack Size
5020.037.210	Black	1/4"	10	M 10 x 1.0	0.24	0.67	0.45	1.36	0.63	0.8818		50 PC
5020.065.203	Black	1/4"	10	M12 x 1.5	0.28	0.79	0.45	1.36	0.63	0.8818		50 PC
5020.037.212	Black	5/16"	13	M12 x 1.5	0.28	0.79	0.47	1.46	0.71	1.1464		50 PC
5020.065.205	Black	5/16"	13	M16 x 1.5	0.39	0.79	0.45	1.46	0.71	1.1905		50 PC
5020.037.216	Black	3/8"	15.8	M16 x 1.5	0.43	0.91	0.45	1.54	0.83	1.5432		50 PC
5020.065.207	Black	3/8"	15.8	M20 x 1.5	0.47	0.98	0.51	1.54	0.83	1.6755		50 PC
5020.037.218	Black	7/16"	18.5	M20 x 1.5	0.53	1.02	0.51	1.65	0.94	1.7637		50 PC
5020.037.220	Black	1/2"	21.2	M20 x 1.5	0.59	1.16	0.51	1.75	1.06	2.4692	X	50 PC
5020.065.209	Black	1/2"	21.2	M25 x 1.5	0.67	1.16	0.51	1.75	1.06	2.7337	X	50 PC
5020.037.225	Black	3/4"	28.5	M25 x 1.5	0.77	1.46	0.51	1.85	1.34	3.7038	X	25 PC
5020.065.211	Black	3/4"	28.5	M32 x 1.5	0.93	1.46	0.59	1.93	1.34	3.9683	X	25 PC
5020.037.232	Black	1"	34.5	M32 x 1.5	1	1.73	0.59	2.01	1.57	5.2911	X	25 PC
5020.037.238	Black	1"	34.5	M40 x 1.5	1.2	1.91	0.59	1.75	1.57	5.6438	X	25 PC
5020.037.240	Black	1 1/4"	42.5	M40 x 1.5	1.26	2.28	0.67	2.99	2.17	12.7868	X	25 PC
5020.037.245	Black	1 1/4"	42.5	M50 x 1.5	1.48	2.48	0.67	2.99	2.36	14.8150	X	25 PC
5020.037.250	Black	1 1/2"	54.5	M50 x 1.5	1.67	2.68	0.67	3.46	2.56	18.2983	X	10 PC
5020.037.263	Black	1 1/2"	54.5	M63 x 1.5	1.93	2.91	0.67	3.46	2.76	22.3769	X	10 PC

"Unsurpassed in Cable Protection and Strain Relief"

2409 Herr St.
Harrisburg, PA 17103