

## 3-5/6 True-RMS Compact Digital Multimeter

Item: **MT-1236**

- Full assortment of test functions
- Precise ACV ACA True RMS Measurements
- Overload Protection
- Non-contact voltage detection
- Includes test leads
- Large backlit screen



LCD Display	3-5/6 5999 Counts
DCV	600mV/6V/60V/600V ± (0.5% +5d)
ACV	600mV/6V/60V/600V ± (1% +4d) <b>TRUE-RMS</b>
DCA	60mA/600mA ± (1.2% +5 d) , 10A± (3.0% +5d)
ACA	60mA/600mA ± (1.5% +5 d) , 10A± (3.0% +5d) <b>TRUE-RMS</b>
Frequency	9.999Hz/99.99Hz/999.9Hz/9.999KHz/99.99KHz/999.9KHz/9.999MHz ± (1.5% +5d)
Duty Cycle	1%~99%± (2.5% +5 d)
ResistanceΩ	600Ω/6k/60k/600k/6M/60MΩ ± (0.8% +5d)
Capacitance	60nF/600nF/6uF/60uF/600uF/6mF ± (4% + 5d) ,100mF ± (4% +10d)
Temperature(C/F)	-20°C~1000°C± (1% + 3d) -4°F~2372°F± (1% + 3d)
Continuity Buzzer	≤30Ω , buzzer beeps
Diode Test	Y
NCV Detection	Y
Data Hold	Y
LED Light	Y
LCD Backlight	Y
Analog Bar	Y
Low Battery Indication	Y
Accessories	Test Lead, K-type thermocouple, Manual
Power	1.5V AAA x 3pcs (Not Included)
Dimensions	5.8 x 3.1 x 1.9 in.
Weight	0.46 lbs (without battery)

**Order Today! [SalesSupport@EclipseTools.com](mailto:SalesSupport@EclipseTools.com)**

Eclipse Enterprises, Inc. • Tel: 804.561.2610 • Fax: 804.561.2642

13302 Chula Road, Amelia Court House, VA 23002 • [EclipseTools.com](http://EclipseTools.com)