




Quality Products. Service Excellence.

## Type 12 Mild Steel Pushbutton Enclosures 1437 Series

Extra Deep



### Application

- Designed to accept standard heavy duty oil tight pushbuttons, switches and pilot lights.
- Provides protection from dirt, dust, oil and water.

### Standards

- UL 508A Type 12 and 13
- CSA Enclosure 12 and 13
- **Complies with**
  - NEMA Type 12 and 13
  - IEC 60529, IP54
- Appropriate components are required to maintain these standards.

### Construction

- Formed from 14 gauge steel except A which is 16 gauge.
- Smooth continuously welded seams.
- Welded brackets provide for enclosure mounting.
- Captive cover screws fasten into threaded, sealed wells.
- Larger enclosures provide internally hinged removable covers, designed to hold the cover open during wiring (see drawings).
- Oil resistant gasket and adhesive.
- A bonding stud is provided on the door and a grounding stud is provided on the enclosure.

### Finish

- Cover and enclosure are phosphatized and finished in ANSI 61 gray powder coating.

### Accessories

- Hole Plugs
- General Accessories

**New and improved PDF part drawing files with more detail now available.**

Click part number in table below to access PDF, DXF, and STEP files.

30.5mm PB Part No.	22.5mm PB Part No.	No. of Holes	H	Enclosure W	D
1437A <sup>1</sup>	1437MA <sup>1</sup>	1	4.00	4.00	4.75
1437B	1437MB	2	6.00	4.00	4.75
1437C	1437MC	3	8.00	4.00	4.75
1437D	1437MD	4	10.00	4.00	4.75

30.5mm PB Part No.	22.5mm PB Part No.	No. of Holes	H	Enclosure		
				W	D	
1437F	1437MF	4	7.25	6.25	4.75	
1437H	1437MH	6	9.50	6.25	4.75	
1437K	1437MK	9	9.50	8.50	4.75	
1437O	1437MO	12	11.75	8.50	4.75	
1437S	1437MS	16	11.75	10.75	4.75	
1437V	1437MV	20	14.00	10.75	4.75	
1437X	1437MX	25	14.00	13.00	4.75	

<sup>1</sup> Not hinged

*Data subject to change without notice*

© 2019. Hammond Manufacturing Ltd. All rights reserved.