

## LINNEA-O-B

~35° + 70° oval beam optimized for 0.5 mm metal sheet or profile. Variant made from PC.

### TECHNICAL SPECIFICATIONS:


Dimensions	285.0 x 40.0 mm
Height	10.5 mm
Fastening	clips
ROHS compliant	yes ⓘ


### MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
LINNEA-O-B	Linear lens	PC	clear	

### ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
F15952_LINNEA-O-B » Box size: 398 x 298 x 265 mm	153	36	36	7.4






See also our general installation guide: [www.ledil.com/installation\\_guide](http://www.ledil.com/installation_guide)

#### PHOTOMETRIC DATA (MEASURED):


**CREE** 

LED XP-E  
 FWHM / FWTM 90.0 + 35.0° / 138.0 + 86.0°  
 Efficiency 81 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




**Helvar**

LED L-iC-282-827-865-011A  
 FWHM / FWTM 91.0 + 39.0° / 139.0 + 84.0°  
 Efficiency 83 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:





**Helvar**

LED LP-282-840-009A 60/300  
 FWHM / FWTM 91.0 + 39.0° / 139.0 + 85.0°  
 Efficiency 83 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:











**Helvar**

LED LS-282-840-011A  
 FWHM / FWTM 92.0 + 39.0° / 140.0 + 86.0°  
 Efficiency 82 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:





#### PHOTOMETRIC DATA (MEASURED):

<p><b>Helvar</b></p> <p>LED LX-282-840-023A</p> <p>FWHM / FWTM 91.0 + 39.0° / 139.0 + 86.0°</p> <p>Efficiency 83 %</p> <p>Peak intensity 0.7 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		
<p><b>MST</b> <i>Your solutions</i></p> <p>LED LinLED 280x24mm 1100lm 8x0 2C 30V Opt G1</p> <p>FWHM / FWTM 88.0 + 37.0° / 137.0 + 83.0°</p> <p>Efficiency 82 %</p> <p>Peak intensity 0.7 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		
<p><b>NICHIA</b></p> <p>LED NFSW757H</p> <p>FWHM / FWTM 92.0 + 41.0° / 140.0 + 89.0°</p> <p>Efficiency 85 %</p> <p>Peak intensity 0.7 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		
<p><b>NICHIA</b></p> <p>LED NFSx757G</p> <p>FWHM / FWTM 87.0 + 38.0° / 140.0 + 85.0°</p> <p>Efficiency 81 %</p> <p>Peak intensity 0.7 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		

#### PHOTOMETRIC DATA (MEASURED):

### OSRAM



LED PL-LIN-IND-Z1 2800 560x24  
 FWHM / FWTM 91.0 + 39.0° / 140.0 + 94.0°  
 Efficiency 87 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



### OSRAM

Opto Semiconductors



LED Duris S5 (2 chip)  
 FWHM / FWTM 90.0 + 38.0° / 138.0 + 86.0°  
 Efficiency 83 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



### OSRAM



Opto Semiconductors

LED Duris S5 (Single chip)  
 FWHM / FWTM 91.0 + 38.0° / 139.0 + 88.0°  
 Efficiency 85 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



### PHILIPS


LED Fortimo LED Strip 1ft 1100lm FC HV4 & LV4  
 FWHM / FWTM 92.0 + 40.0° / 140.0 + 85.0°  
 Efficiency 83 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



#### PHOTOMETRIC DATA (MEASURED):



### PHILIPS

LED Fortimo LED Strip 1ft 650lm FC HV4 & LV4  
 FWHM / FWTM 93.0 + 40.0° / 140.0 + 85.0°  
 Efficiency 83 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:





### SAMSUNG

LED LM561B Plus  
 FWHM / FWTM 88.0 + 37.0° / 137.0 + 83.0°  
 Efficiency 82 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:





### SAMSUNG

LED LT-H282C  
 FWHM / FWTM 88.0 + 33.0° / 136.0 + 84.0°  
 Efficiency 83 %  
 Peak intensity 0.8 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



### SAMSUNG



LED LT-H562C  
 FWHM / FWTM 88.0 + 33.0° / 136.0 + 84.0°  
 Efficiency 83 %  
 Peak intensity 0.8 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



#### PHOTOMETRIC DATA (MEASURED):



### SAMSUNG

LED LT-Q282B  
 FWHM / FWTM 86.0 + 33.0° / 136.0 + 84.0°  
 Efficiency 83 %  
 Peak intensity 0.8 cd/m  
 LEDs/each optic 1  
 Light colour White  
 Required components:





### SAMSUNG

LED LT-S282H  
 FWHM / FWTM 87.0 + 33.0° / 136.0 + 84.0°  
 Efficiency 83 %  
 Peak intensity 0.8 cd/m  
 LEDs/each optic 1  
 Light colour White  
 Required components:





### SAMSUNG

LED LT-S562H  
 FWHM / FWTM 87.0 + 33.0° / 136.0 + 84.0°  
 Efficiency 83 %  
 Peak intensity 0.8 cd/m  
 LEDs/each optic 1  
 Light colour White  
 Required components:



### SAMSUNG



LED LT-V282E  
 FWHM / FWTM 87.0 + 33.0° / 136.0 + 84.0°  
 Efficiency 83 %  
 Peak intensity 0.8 cd/m  
 LEDs/each optic 1  
 Light colour White  
 Required components:





#### PHOTOMETRIC DATA (MEASURED):

### SAMSUNG

LED LT-V562E  
 FWHM / FWTM 87.0 + 33.0° / 136.0 + 84.0°  
 Efficiency 83 %  
 Peak intensity 0.8 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:





LED SEOUL DC 3030  
 FWHM / FWTM 89.0 + 37.0° / 138.0 + 87.0°  
 Efficiency 84 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:





### TRIDONIC

LED LLE G4 24x280mm 1250lm  
 FWHM / FWTM 89.0 + 38.0° / 138.0 + 86.0°  
 Efficiency 83 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



### TRIDONIC

LED LLE G4 24x280mm 2000lm ADV  
 FWHM / FWTM 88.0 + 40.0° / 139.0 + 88.0°  
 Efficiency 83 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:






## PHOTOMETRIC DATA (MEASURED):

### TRIDONIC

LED LLE G4 24x280mm 650lm  
FWHM / FWTM 90.0 + 39.0° / 138.0 + 87.0°  
Efficiency 84 %  
Peak intensity 0.7 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B  
Casic Motor Building  
Shenzhen 518057  
P.R.CHINA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Salo, Finland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)