

SIMATIC IPC677D (Panel PC), 2x10/100/1000 Mbit/s Ethernet; 4x USB V3.0, 1x serial (COM1); Watchdog, temperature and Fan monitoring; RAID controller onboard; 22" Touch (1920x 1080); with front USB XEON E3-1268LV3 (4C/8T, 2.3 (3.3) GHz, 8 MB cache VT-D, AMT); PROFIBUS/MPI CP 5622-compatible); 2 MB buffered SRAM Solid-state drive 240 GB 8 GB DDR3 1600 DIMM; 1x PCIE (X16); 1x PCIE (X4) without expansion (HW) Windows 7 Ultimate 64 bit SP1, MUI (de, en, fr, es, it) without expansion (software) 24 V DC industrial Power supply

General information	
Product type designation	IPC677D
Display	
Design of display	22" TFT touch
Screen diagonal	22 in
Resolution (pixels)	
<ul style="list-style-type: none"> Horizontal image resolution 	1 920 pixel
<ul style="list-style-type: none"> Vertical image resolution 	1 080 pixel
Backlighting	
<ul style="list-style-type: none"> MTBF backlighting (at 25 °C) 	30 000 h
Control elements	
Input device	
<ul style="list-style-type: none"> Mouse, at front 	Front USB 2.0 (500mA)
Touch operation	
<ul style="list-style-type: none"> Design as touch screen 	Yes; analog, resistive
Installation type/mounting	
central design	Yes
Mounting in portrait format possible	Yes
Power loss	
In full configuration	165 W
Dimensions	
Width of the housing front	560 mm
Height of housing front	380 mm
Mounting cutout, width	542 mm
Mounting cutout, height	362 mm
Overall depth	112 mm
<ul style="list-style-type: none"> additional mounting depth (optical drive) 	26 mm
Weights	
Weight, approx.	16 kg
last modified:	3/15/2021 