



BAS70X

Schottky Barrier Diode



Features

- V_R 70V
- I_F 70mA

Typical Applications

- Low Forward Voltage Drop

Mechanical Data

- **Package:** SOD523
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Cathode line denotes the cathode end
- **Marking:** K73

■ Limiting Values (Absolute Maximum Rating)

Item	Symbol	Unit	Conditions	Limit Max
Power Dissipation	P_D	mW		150
Storage Temperature	T_{stg}	°C		-55 to +150
Junction Temperature	T_J	°C		125
DC Reverse Voltage	V_R	V		70
Average Rectified Forward Current	I_{FAV}	mA		70
Non-Repetitive Peak Forward Surge Current @ $t = 8.3ms$	IFSM	A		0.1

■ Electrical Characteristics ($T_a=25^\circ C$ Unless otherwise specified)

Item	Symbol	Unit	Conditions	Min	Max
Breakdown Voltage	V_R	V	$I_R=10\mu A$	70	
Reverse Leakage Current	I_R	nA	$V_R=50V$		100
Forward Voltage ²	V_F	V	$I_F=1mA$		0.41
			$I_F=15mA$		1
Reverse Recovery Time	T_{rr}	ns	$I_F=I_R=10mA$ to $I_R=1mA, R_L=100\Omega$		5
Capacitance	C_j	pF	$V_R=1V, f=1MHz$		2




■ Ordering Information (Example)

PREFERRED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
BAS70X	F2	Approximate 0.0025	8000	80000	320000	7" reel




BAS70X


■ Characteristics(Typical)



■ Outline Dimensions



■ Soldering Footprint





BAS70X

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.