M	ounting Option 116 (2.95) I.D. Floating Eyelets	Contact Detail 500-Wire Hole .087x.013(2.21x0.3 .156 [3.96] Contact Spacing x .140	3) - Tail LG.=.282(7.16) [3.56] Row Spacing	THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MA	STER	ISSUE NUM ORIGINA	
	Card Slot Accepts — .054 (1.37) to .070 (1.78) Thick P.C. Board						
\ <u>\</u>	-0.156[3.96]						
		6.092[154.74] 6.238[158.45] 6.524[165.71]					
						0.330 [8.38] Card Slot	
	A					0.3	
 					<u>†</u>	N N N N N N N N N N N N N N N N N N N	
0.460[11.68] —)		-	0.125[3.18]	II SECTION	۸-A ا
0.460					ACAD REFERENCE I DRAWN: J.LEE CHECKED:	DATE: SEF	
See Accompanying Page for: • Mounting Options YOUR CONNE			EDAC INC TORONTO, ONTARIO CANADA CONNECTION TO QUALITY & SERVICE	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INCAND SHALL NOT BE REPRODUCED, OR COPIEC OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: NTS DRAWING NUMBER 305 Assemble	SHEET	I OF 2

