

Touch panel - TP 5150S - 2403106

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Touch panel with 38.1 cm/15" TFT-display (analog resistive (polyester)), 1024 x 768 pixel(s) (XGA), 16.2 million colors, Intel® Atom™ N455 1.66 GHz, 4x USB 2.0, 1x COM (RS-232/422/485), 2x COM (RS-232), 2x Ethernet (10/100/1000 Mbps), RJ45, Windows® Embedded Compact 7 and user software: Visu+ / AX OPC Server. (bus system: without)

Your advantages

- IP65 degree of protection (front) IP20 degree of protection (back)
- LCD display with resistive touch screen
- Energy-efficient Intel® ATOM™ processors
- Three COM ports
- Fanless design
- Visu+ RT and AX OPC server integrated as standard in all devices



Key Commercial Data

Packing unit	1 pc
GTIN	
GTIN	4055626247915

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Outer dimensions: width, height, depth	410 mm x 309 mm x 55 mm
Installation dimensions: width, height, depth	386.6 mm x 285 mm (Installation cutout)

Display

Display	38.1 cm/15" TFT
Screen resolution	1024 x 768 Pixel(s) (XGA)
Touch technology	analog resistive (polyester)
Brightness	350 cd/m ² , typical (adjustable)

Touch panel - TP 5150S - 2403106

Technical data

Display

Backlighting	CCFL
Display backlight MTBF	> 50000 h
Colors	16.2 million colors

Computer data

Processor	Intel® Atom™ N455 1.66 GHz
Cooling	passive
Operating system	Windows® Embedded Compact 7
User software	Visu+
	AX OPC Server
RAM	2 GB DDR3 SODIMM
Mass storage	CompactFlash®, 2 GB
Network	2x Ethernet (10/100/1000 Mbps), RJ45
Interfaces	4x USB 2.0
	1x COM (RS-232/422/485)
	2x COM (RS-232)
Monitor output	1x VGA
Bus system	without
Realtime clock	Yes (battery-backed)
Service life of battery	5 years (typical)

General

Material front plate	Aluminum die-cast
Mounting type	Installation in front plate
Weight	6.5 kg

Ambient conditions

Degree of protection	IP65 (front), IP20 (back)
Ambient temperature (operation)	0 °C ... 50 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Permissible humidity (operation)	5 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	5 % ... 95 % (non-condensing)
Vibration (operation)	DIN EN 60068-2-6
Shock	15g, 11 ms in accordance with IEC 60068-2-27

Device supply

Supply voltage	24 V DC
Supply voltage range	19.2 V DC ... 28.8 V DC
Power consumption	typ. 12.5 W
Power supply unit	24 V DC ±20 %

Standards and Regulations

Shock	15g, 11 ms in accordance with IEC 60068-2-27
-------	--

Touch panel - TP 5150S - 2403106

Technical data

Standards and Regulations

Vibration (operation)	DIN EN 60068-2-6
-----------------------	------------------

Phoenix Contact 2019 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>