



Click [here](#) for the 3D model.

Dimensions

| | |
|----|--------------------|
| L | 41.5mm +0.6/-0.7mm |
| H | 44mm +0.2/-0.7mm |
| T | 24mm +0.4/-0.7mm |
| S | 37.5mm +/-0.4mm |
| S1 | 10.2mm +/-0.4mm |
| LL | 6mm +0/-2mm |
| F | 1.2mm +/-0.05mm |

Packaging Specifications

| | |
|--------------------|-----------|
| Packaging | Bulk, Box |
| Packaging Quantity | 44 |

General Information

| | |
|------------------|--------------------------------------|
| Series | C4AQ-M |
| Dielectric | Metallized Polypropylene |
| Style | Radial |
| RoHS | Yes |
| Lead | 4 Wire Leads |
| Qualifications | AEC-Q200, IEC61071, EN61071, VDE0560 |
| AEC-Q200 | Yes |
| Component Weight | 61.4 g |
| Miscellaneous | Rth = 17 C/W. |

Specifications

| | |
|-----------------------|---|
| Capacitance | 20 uF |
| Capacitance Tolerance | 5% |
| Voltage DC | 900 VDC |
| Temperature Range | -55/+105°C |
| Rated Temperature | 85°C |
| Insulation Resistance | 1.5 GOhms |
| Max dV/dt | 35 V/us |
| Resistance | 4.3 mOhms (10kHz 70C) |
| Ripple Current | 18.9 Amps Irms (10kHz 70C), 700 Amps Ipkr |
| Inductance | 13 nH |