1000 Eaton Boulevard
Cleveland, OH 44122
United States

SCSI/Fibre Channel - 4-ft. SCSI Cable HD68M to DB25M Double Shielded

MODEL NUMBER: **S402-004**

Highlights

- Premium double-shielded cable
- 34 twisted-pair conductors

System Requirements

- Any external SCSI III device or controller card requiring HD68 or DB25 interface

Package Includes

- 4-ft SCSI cable HD68M to DB25M double shielded

Description

Multi-platform SCSI III external peripheral cable HD68m to DB25M. This 4ft cable is designed to connect two SCSI III (fast SCSI) devices together. Manufactured using double shielded 25 twisted pair high impedance cable. Constructed with low-capacitance, impedance matched, 28 AWG, stranded, tinned copper cable with insulated in polypropylene. Tripp Lite warrants this product to be free from defects in materials and workmanship for life.

Features

- Backwards compatibility with previous SCSI generations
- Double shielded (foil and braid)
- 25 twisted pair conductors
- All Tripp Lite SCSI products, regardless of the SCSI generation, meet the latest specifications of ANSI
- Tripp Lite offers a complete line of internal and external solutions for SCSI/RAID and fibre channel ranging from the very latest Ultra 320 to legacy SCSI-1 and every combination in between
- Tripp Lite warrants this product to be free from defects in materials and workmanship for life

Specifications

OVERVIEW	
UPC Code	037332014108
PHYSICAL	
Cable Length (ft.)	4
Cable Length (m)	1.22
Shipping Dimensions (hwd / in.)	11.75 x 7.00 x 0.75

1000 Eaton Boulevard
Cleveland, OH 44122
United States

Shipping Dimensions (hwd / cm)	29.84 x 17.78 x 1.90
Shipping Weight (lbs.)	0.54
Shipping Weight (kg)	0.24
CONNECTIONS	
Side A - Connector 1	HD68 (MALE)
Side B - Connector 1	DB25 (MALE)
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	Lifetime limited warranty