

## Specification Sheet

Part Number: T30R0VOC2



**Article Number**

111-03072

**Type**

T30R

**Color**

Black (BK)

**Features & Benefits**

- Feature a UL 94 V-0 rating to comply with low flame and smoke requirements.
- Inside serrations provide strong grip on cables and wire bundles.
- Easy application either manually or with a tensioning tool.
- Bent tail ensures a quick and simple installation.

**Quantity Per**

bag

**Product Description**

HellermannTyton's flame retardant cable ties meet the UL 94 V-0 flammability requirements. T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description**

Flame-Retardant Cable Tie, 5.8" Long, UL Rated, 30lb Tensile Strength, PA66V0, Black, 100/pkg

**Global Part Name**

T30R-PA66V0-BK

**Minimum Tensile Strength (Imperial)**

30.0

**Minimum Tensile Strength (Metric)**

135.0

**Length L (Imperial)**

6.0

**Length L (Metric)**

150.0

**Identification Plate Position**

none

**Releasable Closure**

No

**Tie Closure**

plastic pawl

**Variant**

Inside Serrated

**Width W (Imperial)**

0.14

**Width W (Metric)**

3.6

**Bundle Diameter Min (Imperial)**

0.12

**Bundle Diameter Min (Metric)**

3.0

**Bundle Diameter Max (Imperial)**

1.38

**Bundle Diameter Max (Metric)**

35.0

<b>Thickness T (Metric)</b>	1.1
<b>Material</b>	Polyamide 6.6 V0 (PA66V0)
<b>Material Shortcut</b>	PA66V0
<b>Flammability</b>	UL 94 V0
<b>Operating Temperature (Metric)</b>	-40°F to +185°F (-40°C to +85°C)
<b>ROHS Complaint</b>	Yes
<b>Certification/Specification WEB</b>	UL-ZODZ2.E64139
<b>UL Recognized (US)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes
<b>Package Quantity(Imperial)</b>	100
<b>Package Quantity (Metric)</b>	100
<b>Customs Number</b>	3926909988

