

Catalog Number
Project Number
Type

### DESCRIPTION

LED-GIMBAL-PRO Series lights are bright, energy efficient and elegantly designed. They are an ideal solution for commercial and residential applications requiring compact shape, superior quality and visual aesthetics. This 8W light produces 696-784Lm (depending on the CCT). At 1.77" tall and 2.48" round they can fit into tight spaces that a traditional recessed can light can't, such as ceilings with ductwork/piping/obstructions, hot-roof ceilings with limited vertical clearance, and tight soffits. It comes in Black, White and Brushed Nickel Finishes. Each light can be set at 3000K, 4000K or 5000K CCT (Adjustable). These lights feature an easily adjustable LED face (Gimbal) that can be pointed straight downward, making them compatible with sloped ceilings.

Lifespan: 39,000 hrs  
 Certifications: ETL, CE, RoHS  
 Warranty: 5 years

### ELECTRICAL

Lumen output: 696-784 lm  
 Wattage: 8 watts  
 CCT (adjustable): 3000K, 4000K, 5000K  
 Operating voltage: 110-130 VAC  
 Dimming: Dimmable

### MATERIAL / OPTICS

Finish: White, black, brushed nickel  
 Interchangeable trim ring  
 Light direction: Downlight  
 Beam angle: 40 degrees

## 4" RECESSED DIMMABLE ADJUSTABLE CCT LIGHT RCTG-7W-4IN



Diameter	Height
Module - 2.48 in (63 mm) Trim - 4.72 in (120 mm) Cutout (min) - 2.75 in (70 mm) Cutout (max) - 2.88 in (73 mm)	1.77 in (45 mm)

Example: **RCTG-7W-4IN-WH**

Model	Power	Voltage	Trim Size	Finish
<b>RCTG</b>	<b>7W</b> 696-784 lm	<b>110-130 VAC</b>	<b>4IN</b>	<b>WH</b> White <b>B</b> Black <b>N</b> Brushed Nickel

TRIM OPTIONS

---



BRUSHED NICKEL



BLACK



WHITE

RECESSED LIGHT AND DRIVER

---



PHOTOMETRICS

---

