


	RUN	UVLO	SHDN
JP1	1	1	0
JP2	1	0	X

*** VERSION TABLE**

Assembly Version	U1	VFLOAT*
DC1473A - A	LT3650EDD - 8.4	8.4V
DC1473A - B	LT3650EDD - 8.2	8.2V

Unless noted:
Resistors: Ohms
 0402
 1%
 1/16W
Capacitors:
 0402
 10%
 10V

CUSTOMER NOTICE		CONTRACT NO.		 1630 McCarthy Blvd. Milpitas, CA 95035 Phone: (408)432-1900 Fax: (408)434-0507
LINEAR TECHNOLOGY HAS MADE A BEST EFFORT TO DESIGN A CIRCUIT THAT MEETS CUSTOMER-SUPPLIED SPECIFICATIONS; HOWEVER, IT REMAINS THE CUSTOMER'S RESPONSIBILITY TO VERIFY PROPER AND RELIABLE OPERATION IN THE ACTUAL APPLICATION. COMPONENT SUBSTITUTION AND PRINTED CIRCUIT BOARD LAYOUT MAY SIGNIFICANTLY AFFECT CIRCUIT PERFORMANCE OR RELIABILITY. CONTACT LINEAR TECHNOLOGY APPLICATIONS ENGINEERING FOR ASSISTANCE. THIS CIRCUIT IS PROPRIETARY TO LINEAR TECHNOLOGY AND SUPPLIED FOR USE WITH LINEAR TECHNOLOGY PARTS.		APPROVALS DRAWN J.Drew 8/25/08 CHECKED APPROVED ENGINEER J.Drew 8/25/08 DESIGNER	DATE 8/25/08	
TITLE LT3650EDD - 8.4, LT3650EDD - 8.2 2A Monolithic 2 Cell Li-Ion Battery Charger				REV A
SIZE A	CAGE CODE	DWG NO DC1473A - A/B	SCALE:	FILENAME:
Tuesday, April 14, 2009		SHEET 1 OF 1		