



General Information

| | |
|------------------|--------------------------|
| Series | F873 |
| Dielectric | Metallized Polypropylene |
| Style | Radial |
| Features | MKP EMI Safety |
| RoHS | Yes |
| Lead | Wire Leads |
| Safety Class | X1 |
| Qualifications | ENEC, UL, cUL, CQC |
| AEC-Q200 | No |
| THB Performance | No |
| Component Weight | 2.662 g |
| Miscellaneous | ClimCat: 40/110/56/B. |
| Shelf Life | 104 Weeks |

Click [here](#) for the 3D model.

Dimensions

| | |
|----------------|--------------------|
| L | 26mm -0.5mm |
| H | 14.5mm -0.5mm |
| T | 6mm -0.5mm |
| S | 22.5mm +0.6/-0.1mm |
| H ₀ | 18.5mm +/-0.5mm |
| F | 0.8mm +/-0.05mm |
| G | 0.5mm NOM |

Packaging Specifications

| | |
|--------------------|-------------------------|
| Packaging | Ammo, 360x340x59mm, Box |
| Packaging Quantity | 464 |

Specifications

| | |
|-----------------------|--------------|
| Capacitance | 0.022 uF |
| Capacitance Tolerance | 10% |
| Voltage AC | 760 VAC (X1) |
| Voltage DC | 1500 VDC |
| Temperature Range | -40/+110°C |
| Rated Temperature | 110°C |
| Dissipation Factor | 0.1% 1kHz |
| Insulation Resistance | 30 GOhms |
| Max dV/dt | 300 V/us |